

ASEG Extended Abstracts >

Volume 2007, 2007 - [Issue 1: ASEG2007 - 19th Geophysical Conference](#)

✔ Free access

59 Views | 4 CrossRef citations to date | 0 Altmetric

Articles

# Land Seismic Acquisition Repeatability for Time-Lapse Monitoring of CO<sub>2</sub> Sequestration

Milovan Urosevic, Don Sherlock, Anton Kepic & Kevin Dodds

Page 1 | Published online: 09 Dec 2019

🗨️ Cite this article 🔗 <https://doi.org/10.1071/ASEG2007ab131>

Sample our  
Earth Sciences  
Journals

>> [Sign in here](#) to start your access  
to the latest two volumes for 14 days

🗨️ Citations

📊 Metrics

🖨️ Reprints & Permissions

📄 View PDF

🔗 Share

## Abstract

Time-lapse surface and borehole seismic surveys are planned for monitoring the injection of CO<sub>2</sub> in the CO<sub>2</sub>CRC Otway Basin Pilot Project in Victoria. Critical to the success of this is to ensure optimum repeatability of acquisition parameters and ground conditions. In order to assess the relative influences of source types and environmental conditions, a series of repeated test surveys have been undertaken.

The study utilised repeated high-resolution seismic surveys along the same 2D line. The first test line was acquired with mini-vibroseis (6000 lb) in wet conditions when the top soil and the weathered layers were fully saturated. The line was subsequently re-recorded in dry conditions where we utilised the same mini-vibrator, but in addition repeated the line using a free-fall weight drop. Both sources have similar total energy

output but a vibrator is a controlled frequency source while a weight drop is not. Despite differences in the frequency content and phase of the signal generated by these two sources, and positioning differences for source and receiver locations of up to 1m, almost identical stacked sections were obtained after phase matching and scaling of the two datasets. Far greater differences in total energy, frequency content and phase of the signal were observed between the two vibroseis lines recorded at different times of the year (wet and dry periods).

Our results clearly demonstrate that near surface conditions has a first order effect on repeatability of land seismic surveys. A common belief that deployment of the same seismic source and positioning errors are crucial for successful time-lapse seismic needs to be reexamined in light of our results, which show that these factors are of secondary importance when it comes to land seismic surveys.

Technical Area: Time-lapse/CO2 sequestration, Seismic acquisition

---

## Article PDF

Loading PDF viewer...

[Download PDF](#)

## Related research

Recommended articles

Cited by  
4

[Evaluation of real-time PPP techniques for seismic and structural monitoring >](#)

Mert Bezioglu et al.

Survey Review

Published online: 2 Feb 2026

[CO<sub>2</sub> sequestration through alkali-activated steel slag: a review >](#)

Senthil Kumar Kaliyavaradhan et al.

Journal of Sustainable Cement-Based Materials

Published online: 5 Dec 2024

[GNSS dynamic monitoring and time-frequency feature analysis in structural seismic response assessment >](#)

Ling'ai Li et al.

All Earth

Published online: 5 Nov 2025



[View more](#)

## Information for

[Authors](#)

[R&D professionals](#)

[Editors](#)

[Librarians](#)

[Societies](#)

## Opportunities

[Reprints and e-prints](#)

[Advertising solutions](#)

[Accelerated publication](#)

[Corporate access solutions](#)

## Open access

[Overview](#)

[Open journals](#)

[Open Select](#)

[Dove Medical Press](#)

[F1000Research](#)

## Help and information

[Help and contact](#)

[Newsroom](#)

[All journals](#)

[Books](#)

## Keep up to date

Register to receive personalised research and resources by email



Sign me up



Copyright © 2026 Informa UK Limited [Privacy policy](#)

[Cookies](#) [Terms & conditions](#) [Accessibility](#)

Registered in England & Wales No. 01072954  
5 Howick Place | London | SW1P 1WG



**Taylor & Francis**  
by informa