



ASEG Extended Abstracts >

Volume 2007, 2007 - [Issue 1](#): ASEG2007 - 19th Geophysical Conference



Free access

40

Views

3

CrossRef citations to date

0

Altmetric

Articles

# Land Seismic Acquisition Repeatability for Time-Lapse Monitoring of CO<sub>2</sub> Sequestration

Milovan Urosevic, Don Sherlock, Anton Kepic & Kevin Dodds

Page 1 | Published online: 09 Dec 2019

Cite this article <https://doi.org/10.1071/ASEG2007ab131>

Sample our  
Earth Sciences  
Journals



>> [Sign in here](#) to start your access  
to the latest two volumes for 14 days

## We Care About Your Privacy

We and our 907 partners store and access personal data, like browsing data or unique identifiers, on your device. Selecting "I Accept" enables tracking technologies to support the purposes shown under "we and our partners process data to provide," whereas selecting "Reject All" or withdrawing your consent will disable them. If trackers are disabled, some content and ads you see may not be as relevant to you. You can resurface this menu to change your choices or withdraw consent at any time by clicking the ["privacy preferences"] link on the bottom of the webpage [or the floating icon on the bottom-left of the webpage, if applicable]. Your choices will have effect within our Website. For more details, refer to our Privacy Policy. [Here](#)

We and our partners process data to provide:

...

I Accept

Reject All

Show Purpose of the



the  
to the  
s and ground  
environmental  
2D line. The  
when the top  
tly re-  
addition  
tal energy  
not.

Despite differences in the frequency content and phase of the signal generated by these two sources, and positioning differences for source and receiver locations of up to 1m, almost identical stacked sections were obtained after phase matching and scaling of the two datasets. Far greater differences in total energy, frequency content and phase of the signal were observed between the two vibroseis lines recorded at different times of the year (wet and dry periods).

Our results clearly demonstrate that near surface conditions has a first order effect on repeatability of land seismic surveys. A common belief that deployment of the same seismic source and positioning errors are crucial for successful time-lapse seismic needs to be reexamined in light of our results, which show that these factors are of secondary importance when it comes to land seismic surveys.

Technical Area: Time-lapse/CO2 sequestration, Seismic acquisition

[Download PDF](#)

[Share](#)

Related

CO<sub>2</sub> sequestration

Senthil  
Journal of  
Published

Use  
study

Behsha  
Soil and  
Published

Boostin

View more

## Information for

Authors  
R&D professionals  
Editors  
Librarians  
Societies

## Opportunities

Reprints and e-prints  
Advertising solutions  
Accelerated publication  
Corporate access solutions

## Open access

Overview  
Open journals  
Open Select  
Dove Medical Press  
F1000Research

## Help and information

Help and contact  
Newsroom  
All journals  
Books

## Keep up to date

Register to receive updates  
by email



Sign up



Copyright

Acc

Registered  
5 Howick Pl



or & Francis Group  
orma business