

ASEG Extended Abstracts >

Volume 2007, 2007 - Issue 1: ASEG2007 - 19th Geophysical Conference

Free access

32 Views | 3 CrossRef citations to date | 0 Altmetric

Articles

Land Seismic Acquisition Repeatability for Time-Lapse Monitoring of CO2 Sequestration


Milovan Urosevic, Don Sherlock, Anton Kepic & Kevin Dodds

Page 1 | Published online: 09 Dec 2019

Cite this article <https://doi.org/10.1071/ASEG2007ab131>

Sample our Earth Sciences Journals

>> [Sign in here](#) to start your access to the latest two volumes for 14 days



Citation

Abstract

Time-lapse

injection

success

condit

cond

The stud

first test

soil and

recorded

repeated

output b

We Care About Your Privacy

We and our 878 partners store and access personal data, like browsing data or unique identifiers, on your device. Selecting I Accept enables tracking technologies to support the purposes shown under we and our partners process data to provide. Selecting Reject All or withdrawing your consent will disable them. If trackers are disabled, some content and ads you see may not be as relevant to you. You can resurface this menu to change your choices or withdraw consent at any time by clicking the Show Purposes link on the bottom of the webpage. Your choices will have effect within our Website. For more details, refer to our Privacy Policy. [Here](#)

We and our partners process data to provide:

Use precise geolocation data. Actively scan device

I Accept

Reject All

Show Purpose



g the
to the
s and ground
vironmental

2D line. The
hen the top
tly re-
addition
tal energy
not.

Despite differences in the frequency content and phase of the signal generated by these two sources, and positioning differences for source and receiver locations of up to 1m, almost identical stacked sections were obtained after phase matching and scaling of the two datasets. Far greater differences in total energy, frequency content and phase of the signal were observed between the two vibroseis lines recorded at different times of the year (wet and dry periods).

Our results clearly demonstrate that near surface conditions has a first order effect on repeatability of land seismic surveys. A common belief that deployment of the same seismic source and positioning errors are crucial for successful time-lapse seismic needs to be reexamined in light of our results, which show that these factors are of secondary importance when it comes to land seismic surveys.

Technical Area: Time-lapse/CO2 sequestration, Seismic acquisition

[Download PDF](#)

Related research

Recommended articles

Cited by



Information for

- Authors
- R&D professionals
- Editors
- Librarians
- Societies

Opportunities

- Reprints and e-prints
- Advertising solutions
- Accelerated publication
- Corporate access solutions

Keep up to date

Register to receive personalised research and resources by email

 Sign me up

- 
- 
- 
- 
- 

Open access

- Overview
- Open journals
- Open Select
- Dove Medical Press
- F1000Research

Help and information

- Help and contact
- Newsroom
- All journals
- Books

