








▶ All Journals ▶ ASEG Extended Abstracts ▶ List of Issues ▶ Volume 2007, Issue 1 ► Land Seismic Acquisition Repeatability f

ASEG Extended Abstracts >

Volume 2007, 2007 - Issue 1: ASEG2007 - 19th Geophysical Conference



Views CrossRef citations to date Altmetric

Articles

Land Seismic Acquisition Repeatability for Time-Lapse Monitoring of CO2 Sequestration

Milovan Urosevic, Don Sherlock, Anton Kepic & Kevin Dodds

Page 1 | Published online: 09 Dec 2019

66 Cite this article ▲ https://doi.org/10.1071/ASEG2007ab131

Sample our

66 Citations

Metrics

Reprints & Permissions

冈 View PDF

Abstract

Time-lap

success

conditio

conditio

The s

We Care About Your Privacy injection

> We and our 845 partners store and/or access information on a device, such as unique IDs in cookies to process personal data. You may accept or manage your choices by clicking below, including your right to object where legitimate interest is used, or at any time in the privacy policy page. These choices will be signaled to our partners and will not

affect browsing data. Privacy Policy

We and our partners process data to provide:

Use precise geolocation data. Actively scan device characteristics for identification. Store and/or access information on a device. Personalised advertising and content, advertising and content measurement, audience

research and services development.

2D line. The hen the top tly readdition tal energy

g the

Essential Onlvironmental

to the

and ground

I Accept

Show Purpose

not.

ated by

first \ soil and recorded repeated

output b

Despite

List of Partners (vendors)

these two sources, and positioning differences for source and receiver locations of up to 1m, almost identical stacked sections were obtained after phase matching and scaling of the two datasets. Far greater differences in total energy, frequency content and phase of the signal were observed between the two vibroseis lines recorded at different times of the year (wet and dry periods).

Our results clearly demonstrate that near surface conditions has a first order effect on repeatability of land seismic surveys. A common belief that deployment of the same seismic source and positioning errors are crucial for successful time-lapse seismic needs to be reexamined in light of our results, which show that these factors are of secondary importance when it comes to land seismic surveys.

Technical Area: Time-lapse/CO2 sequestration, Seismic acquisition Download PDF Related research 1 Recommended articles Cited by X

Information for Open access Authors Overview R&D professionals Open journals Editors **Open Select** Librarians **Dove Medical Press** Societies F1000Research Opportunities Help and information Reprints and e-prints Advertising solutions Newsroom Accelerated publication Corporate access solutions Books Keep up to date Register to receive personalised research and resources by email Sign me up Taylor & Francis Group Copyright © 2024 Informa UK Limited Privacy policy Cookies Terms & conditions Accessib X

