









Abstract

Full Article

➡ Reprints & Permissions

Figures & data

A sandbag microstructure was constructed in polyamide 6 (PA6)/ethylene– propylene–diene terpolymer (EPDM)/nanometer calcium carbonate (nano-CaCO₃) ternary composites by the addition of maleinated EPDM (EPDM-g-MA) to reduce the interfacial tension between EPDM and PA6 and EPDM and nano-CaCO₃. Scanning electron microscopy observation and differential scanning calorimetry analysis revealed that the microstructure of the ternary composites evolved from the initially separated EPDM and nano-CaCO₃ dispersion structure to the sandbag structure and finally to the separated dispersion structure again with the increase of EPDM-g-MA content in the elastomer

to the latest two volumes for 14 days

66 Citations

Share

Metrics

References

Read this article

phase. The mechanical results showed the composites with the sandbag microstructure exhibited excellent toughness and stiffness.

Keywords:

EPDM-g-MA interface tension PA6 nanoparticle sandbag microstructure ternary composite

Acknowledgements

The authors gratefully acknowledge the financial support of this work by the Nature Science Foundation of China (contract number: 50573067).



Related research 1

People also read Recommended articles

Cited by 1

Information for

Authors

R&D professionals

Editors

Librarians

Societies

Opportunities

Reprints and e-prints

Advertising solutions

Accelerated publication

Corporate access solutions

Open access

Overview

Open journals

Open Select

Dove Medical Press

F1000Research

Help and information

Help and contact

Newsroom

All journals

Books

Keep up to date

Register to receive personalised research and resources by email



Sign me up











Accessibility



Copyright © 2025 Informa UK Limited Privacy policy Cookies Terms & conditions



Registered in England & Wales No. 01072954 5 Howick Place | London | SW1P 1WG