



Separation Science and Technology >

Volume 55, 2020 - [Issue 7](#)

290 | 5
Views | CrossRef citations to date | Altmetric

Natural Gas Processing

Recovery enhancement of liquid hydrocarbons in dew point control unit of natural gas processing plant

Ali Jalali, Marzieh Lotfi , Sara Zilabi & Amir H Mohammadi

Pages 1407-1414 | Received 14 Aug 2018, Accepted 04 Mar 2019, Published online: 31 Mar 2019

Cite this article <https://doi.org/10.1080/01496395.2019.1591450>

Check for updates

Sample our
Physical Sciences
Journals
>> **Sign in here** to start your access
to the latest two volumes for 14 days

Full Article

Figures & data

References

Citations

Metrics

Reprints & Permissions

Read this article

Share

ABSTRACT

The low temperature absorption method is currently used in a gas-processing unit to control the natural gas dew point. The major problem of this unit is the simultaneous absorption of high amount of methane within heavier hydrocarbons, which leads to low purity of ethane and propane streams. Considering the operational conditions, the mentioned method used in second and third phases, will control the dew point at -23°C at the best condition. This temperature is not proper for dew point and shows very high amount of hydrocarbons in product gas. In this study, a new process has been introduced in order to drop the gas liquid dew point (natural gas liquid) to -85°C by self-refrigeration technology. Due to the advanced nature of absorption process, the problem of methane existence in the product of gas liquids is noticeably overcome. In this process, natural gas enters the turbo expander after passing through a

refrigeration cycle at -37°C and it is then expanded in an isotropic process to 2896 kPa pressure. Expander outlet with reflux and condensate produced from a cold separator are fed to an absorption tower with a reboiler and the separation will occur. The advantage of this method is controlling the concentration of methane in the product streams. Simulation results show that the process can daily produce 22,280 barrels of gas liquids with a concentration of 0.5 mole% of methane. In addition, the recovery efficiencies of propane and butane in the newly proposed method are 97.3% and 99.99%, respectively, which show a remarkable advantage over the current trend.

KEYWORDS:

Self-refrigeration

turbo expander

absorption

gas liquids

dew point

Related research

People also read

Recommended articles

Cited by

5

Information for

Authors

R&D professionals

Editors

Librarians

Societies

Opportunities

Reprints and e-prints

Advertising solutions

Accelerated publication

Corporate access solutions

Open access

Overview

Open journals

Open Select

Dove Medical Press

F1000Research

Help and information

Help and contact

Newsroom

All journals

Books

Keep up to date

Register to receive personalised research and resources
by email

 Sign me up

  

  

Copyright © 2025 Informa UK Limited Privacy policy Cookies Terms & conditions

Accessibility



Registered in England & Wales No. 01072954
5 Howick Place | London | SW1P 1WG