

186 Views | 1 CrossRef citations to date | 0 Altmetric


Natural Gas Processing

# Recovery enhancement of liquid hydrocarbons in dew point control unit of natural gas processing plant

Ali Jalali, Marzieh Lotfi ✉, Sara Zilabi &amp; Amir H Mohammadi ✉

Pages 1407-1414 | Received 14 Aug 2018, Accepted 04 Mar 2019, Published online: 31 Mar 2019

Cite this article https://doi.org/10.1080/01496395.2019.1591450



Sample our  
Physical Sciences  
Journals

>> Sign in here to start your access  
to the latest two volumes for 14 days

Full Article Figures & data References Citations Metrics

Reprints & Permissions **Read this article**

## ABSTRACT

The low temperature absorption method is currently used in a gas-processing unit to control the natural gas dew point. The major problem of this unit is the simultaneous absorption of high amount of methane within heavier hydrocarbons, which leads to low purity of ethane and propane streams. Considering the operational conditions, the

### About Cookies On This Site

We and our partners use cookies to enhance your website experience, learn how our site is used, offer personalised features, measure the effectiveness of our services, and tailor content and ads to your interests while you navigate on the web or interact with us across devices. You can choose to accept all of these cookies or only essential cookies. To learn more or manage your preferences, click "Settings". For further information about the data we collect from you, please see our [Privacy Policy](#).

Accept All

Essential Only

Settings

point at  $-23^{\circ}$ 

ows very

as been

 $85^{\circ}$  c by

cess, the

ercome. In

to 2896 kPa

pressure. Expander outlet with reflux and condensate produced from a cold separator

are fed to an absorption tower with a reboiler and the separation will occur. The advantage of this method is controlling the concentration of methane in the product streams. Simulation results show that the process can daily produce 22,280 barrels of gas liquids with a concentration of 0.5 mole% of methane. In addition, the recovery efficiencies of propane and butane in the newly proposed method are 97.3% and 99.99%, respectively, which show a remarkable advantage over the current trend.

KEYWORDS: Self-refrigeration turbo expander absorption gas liquids dew point


Related research 

People also read	Recommended articles	Cited by 1
Modeling of CO2 capture from gas stream emissions of petrochemical industries by membrane contactor >		
Ali Jalali et al. Petroleum Science and Technology Published online: 8 Aug 2018		



About Cookies On This Site

We and our partners use cookies to enhance your website experience, learn how our site is used, offer personalised features, measure the effectiveness of our services, and tailor content and ads to your interests while you navigate on the web or interact with us across devices. You can choose to accept all of these cookies or only essential cookies. To learn more or manage your preferences, click “Settings”. For further information about the data we collect from you, please see our [Privacy Policy](#).

- Accept All 
- Essential Only
- Settings

## Information for

Authors

R&D professionals

Editors

Librarians

Societies

## Opportunities

Reprints and e-prints

Advertising solutions

Accelerated publication

Corporate access solutions

## Open access

Overview

Open journals

Open Select

Dove Medical Press

F1000Research

## Help and information

Help and contact

Newsroom

All journals

Books

## Keep up to date

Register to receive personalised research and resources by email



Sign me up



Copyright © 2024 Informa UK Limited [Privacy policy](#) [Cookies](#) [Terms & conditions](#)

[Accessibility](#)



Taylor & Francis Group  
an informa business

Registered in England & Wales No. 3099067  
5 Howick Place | London | SW1P 1WG

### About Cookies On This Site

We and our partners use cookies to enhance your website experience, learn how our site is used, offer personalised features, measure the effectiveness of our services, and tailor content and ads to your interests while you navigate on the web or interact with us across devices. You can choose to accept all of these cookies or only essential cookies. To learn more or manage your preferences, click “Settings”. For further information about the data we collect from you, please see our [Privacy Policy](#).

Accept All

Essential Only

Settings