

270 5 0
Views CrossRef citations to date Altmetric


Natural Gas Processing

Recovery enhancement of liquid hydrocarbons in dew point control unit of natural gas processing plant

Ali Jalali, Marzieh Lotfi , Sara Zilabi & Amir H Mohammadi 

Pages 1407-1414 | Received 14 Aug 2018, Accepted 04 Mar 2019, Published online: 31 Mar 2019

 Cite this article  <https://doi.org/10.1080/01496395.2019.1591450>



Sample our
Physical Sciences
Journals
>> [Sign in here](#) to start your access
to the latest two volumes for 14 days

 Full Article  Figures & data  References  Citations  Metrics

 Reprints

We Care About Your Privacy

We and our 894 partners store and access personal data, like browsing data or unique identifiers, on your device. Selecting I Accept enables tracking technologies to support the purposes shown under we and our partners process data to provide. Selecting Reject All or withdrawing your consent will disable them. If trackers are disabled, some content and ads you see may not be as relevant to you. You can resurface this menu to change your choices or withdraw consent at any time by clicking the Show Purposes link on the bottom of the webpage. Your choices will have effect within our Website. For more details, refer to our Privacy Policy. [Here](#)

We and our partners process data to provide:

Use precise geolocation data. Actively scan device

 I Accept

Reject All

Show Purpose



ABSTRA

The low
control t
absorpti
purity
ment
c at the
high am
introduc
self-refri
problem
this proc

ng unit to
ultaneous
leads to low
ns, the
oint at -23°
ows very
as been
 -85° c by
cess, the
ercome. In

refrigeration cycle at -37° c and it is then expanded in an isotropic process to 2896 kPa

pressure. Expander outlet with reflux and condensate produced from a cold separator are fed to an absorption tower with a reboiler and the separation will occur. The advantage of this method is controlling the concentration of methane in the product streams. Simulation results show that the process can daily produce 22,280 barrels of gas liquids with a concentration of 0.5 mole% of methane. In addition, the recovery efficiencies of propane and butane in the newly proposed method are 97.3% and 99.99%, respectively, which show a remarkable advantage over the current trend.

KEYWORDS:


Self-refrigeration

turbo expander

absorption

gas liquids

dew point



×



AI ASSISTANT
for Chemistry

TRY IT FREE
FOR 7 DAYS

**OPTIMIZE
YOUR
RESEARCH
WITH
CHEMY
LANE**

Related research 



Information for

- Authors
- R&D professionals
- Editors
- Librarians
- Societies

Opportunities

- Reprints and e-prints
- Advertising solutions
- Accelerated publication
- Corporate access solutions

Open access

- Overview
- Open journals
- Open Select
- Dove Medical Press
- F1000Research

Help and information

- Help and contact
- Newsroom
- All journals
- Books

Keep up to date

Register to receive personalised research and resources by email

 Sign me up



Copyright

Accessib

Registered
5 Howick Pl

or & Francis Group
orma business

