



Materials and Manufacturing Processes >

Volume 23, 2007 - [Issue 1](#)

1,137

Views

136

CrossRef citations to date

0

Altmetric

Original Articles

# Optimization of Plasma Arc Welding Parameters by Using the Taguchi Method with the Grey Relational Analysis

Y. F. Hsiao, Y. S. Tarn & W. J. Huang

Pages 51-58 | Received 18 Aug 2006, Accepted 20 Dec 2006, Published online: 14 Dec 2007

Cite this article <https://doi.org/10.1080/10426910701524527>

Sample our  
Physical Sciences  
Journals



>> [Sign in here](#) to start your access  
to the latest two volumes for 14 days

Full Article

Figures & data

References

Citations

Metrics

Reprints & Permissions

Read this article

Share

## Abstract

The optimal parameters process of plasma arc welding (PAW) by the Taguchi method with Grey relational analysis is studied. The Grey relational grade is used to find optimal PAW parameters with multiple response performance characteristics. The welding parameters (welding current, welding speed, plasma gas flow rate, and torch stand-off) are optimized with consideration of the multiple response performance characteristics (the penetration of root, the weld groove width, and the weld pool undercut). As a result, the improvement percentage of the Grey relational grade with the multiple response performance characteristics is 31.8%. It is shown that the multiple response performance characteristics are greatly improved through this study.

Keywords:

Analysis of variance (ANOVA)

Dyeing machinery

Grey relational analysis

Keyhole

Multiple performance

Optimization

Orthogonal array

Penetration

Plasma arc welding (PAW)

S/N ratio

Taguchi method

Torch stand-off

Undercut

Welding current

## Notes

Total mean value of the grey relational grade = 0.5517.

### Related Research Data

Process parameter selection for optimizing the weld pool geometry in the tungsten inert gas welding of stainless steel

Source: Journal of Materials Processing Technology

Use of the Taguchi Method and Grey Relational Analysis to Optimize Turning Operations with Multiple Performance Characteristics

Source: Materials and Manufacturing Processes

Optimising removal rate and reliability of polishing of ceramic blocks using a combination of Taguchi and grey methods

Source: Materials Science and Technology

Optimization of machining parameters of Wire-EDM based on Grey relational and statistical analyses

Source: International Journal of Production Research

Fisher, R. A.: Statistical Methods for Research Workers, 14. Aufl., Oliver & Boyd, Edinburgh, London 1970. XIII, 362 S., 12 Abb., 74 Tab., 40 s

Source: Biometrische Zeitschrift

## Related research

People also read

Recommended articles

Cited by  
136

Experimental studies on key-hole plasma arc welding process parameters of AISI 304 HCu stainless steel tube joints >

## Information for

[Authors](#)  
[R&D professionals](#)  
[Editors](#)  
[Librarians](#)  
[Societies](#)

## Opportunities

[Reprints and e-prints](#)  
[Advertising solutions](#)  
[Accelerated publication](#)  
[Corporate access solutions](#)

## Keep up to date

Register to receive personalised research and resources by email



Sign me up



Copyright © 2026 Informa UK Limited [Privacy policy](#)

[Cookies](#) [Terms & conditions](#) [Accessibility](#)

Registered in England & Wales No. 01072954  
5 Howick Place | London | SW1P 1WG

## Open access

[Overview](#)  
[Open journals](#)  
[Open Select](#)  
[Dove Medical Press](#)  
[F1000Research](#)

## Help and information

[Help and contact](#)  
[Newsroom](#)  
[All journals](#)  
[Books](#)



**Taylor & Francis**  
by **informa**...