Taylor & Francis
Online

Petroleum Science and Technology ›
Volume 33, 2015 - Issue 12

1,025 Views | 81 CrossRef citations to date | 0 Altmetric

Original Articles

Effects of Nanoparticle Types on Carbon Dioxide Foam Flooding in Enhanced Oil Recovery

M. A. Manan, S. Farad, A. Piroozian & M. J. A. Esmail

Pages 1286-1294 | Published online: 17 Aug 2015

Cite this article https://doi.org/10.1080/10916466.2015.1057593

Check for updates

Sample our Economics, Finance, Business & Industry Journals
>> Sign in here to start your access to the latest two volumes for 14 days

Full Article Figures & data References Citations Metrics
Reprints & Permissions Read this article Share

Abstract

Enhancement of foam stability has been recently evidenced with addition of nanoparticles (NPs), especially in the case of CO_2 foams. Stabilized foams via solid NPs can potentially withstand high reservoirs temperatures. Studies have been conducted to examine the effect of NPs on foam stability; however, more research is required for various types of NPs. Therefore, the authors aimed to investigate the performance of silicon dioxide (SiO_2), aluminum oxide (Al_2O_3), copper oxide (CuO), and titanium dioxide (TiO_2) of different sizes in the presence of fixed concentration of anionic surfactant (AOS) on foam stability. Nano particle concentrations of (0.1 wt%, 0.3 wt%, 0.5 wt%, and 1 wt%) were used to investigate the foam stability, displacement test were performed to determine oil recovery at the optimum concentrations for each nanoparticle. The stability of the aqueous foam was evaluated by the Ross-Miles

method using half-life measurements. All experiments were conducted at room temperature and pressure. The results revealed that all different NPs used were able to improve the stability of CO_2 foam at certain concentrations. However, aluminum oxide NPs showed better results compared to others in terms of foam stability and half-life time. In addition, 0.1 wt% of all NPs types gave the highest foam stability and half-life time. In conclusion, a low concentration of NPs is recommended regardless of type for improving form stability.

Keywords:

foam stability | nanoparticle | enhanced oil recovery | immiscible flooding | surfactant

Related research

People also read | Recommended articles | Cited by 81

Information for

- Authors
- R&D professionals
- Editors
- Librarians
- Societies

Open access

- Overview
- Open journals
- Open Select
- Dove Medical Press
- F1000Research

Opportunities

- Reprints and e-prints
- Advertising solutions
- Accelerated publication
- Corporate access solutions

Help and information

- Help and contact
- Newsroom
- All journals
- Books

Keep up to date

Register to receive personalised research and resources by email

Sign me up

Copyright © 2026 Informa UK Limited Privacy policy

Cookies Terms & conditions Accessibility

Registered in England & Wales No. 01072954
5 Howick Place | London | SW1P 1WG