



Petroleum Science and Technology >

Volume 33, 2015 - [Issue 12](#)

1,015 77

Views | CrossRef citations to date | Altmetric

0

Original Articles

Effects of Nanoparticle Types on Carbon Dioxide Foam Flooding in Enhanced Oil Recovery

M. A. Manan, S. Farad, A. Piroozian  & M. J. A. Esmail

Pages 1286-1294 | Published online: 17 Aug 2015

 Cite this article  <https://doi.org/10.1080/10916466.2015.1057593>



Sample our
Engineering & Technology
Journals
>> [Sign in here](#) to start your access
to the latest two volumes for 14 days

 Full Article

 Figures & data

 References

 Citations

 Metrics

 Reprints & Permissions

[Read this article](#)

[Share](#)

Abstract

Enhancement of foam stability has been recently evidenced with addition of nanoparticles (NPs), especially in the case of CO₂ foams. Stabilized foams via solid NPs can potentially withstand high reservoirs temperatures. Studies have been conducted to examine the effect of NPs on foam stability; however, more research is required for various types of NPs. Therefore, the authors aimed to investigate the performance of silicon dioxide (SiO₂), aluminum oxide (Al₂O₃), copper oxide (CuO), and titanium dioxide (TiO₂) of different sizes in the presence of fixed concentration of anionic surfactant (AOS) on foam stability. Nano particle concentrations of (0.1 wt%, 0.3 wt%, 0.5 wt%, and 1 wt%) were used to investigate the foam stability, displacement test were performed to determine oil recovery at the optimum concentrations for each nanoparticle. The stability of the aqueous foam was evaluated by the Ross-Miles

method using half-life measurements. All experiments were conducted at room temperature and pressure. The results revealed that all different NPs used were able to improve the stability of CO₂ foam at certain concentrations. However, aluminum oxide NPs showed better results compared to others in terms of foam stability and half-life time. In addition, 0.1 wt% of all NPs types gave the highest foam stability and half-life time. In conclusion, a low concentration of NPs is recommended regardless of type for improving form stability.

Keywords:

foam stability

nanoparticle

enhanced oil recovery

immiscible flooding

surfactant

Related research

People also read

Recommended articles

Cited by
77

[The Incorporation of Silica Nanoparticle and Alpha Olefin Sulphonate in Aqueous CO₂ Foam: Investigation of Foaming Behavior and Synergistic Effect >](#)

F. AttarHamed et al.

Petroleum Science and Technology

Published online: 2 Sep 2014

Information for

[Authors](#)

[R&D professionals](#)

[Editors](#)

[Librarians](#)

[Societies](#)

Opportunities

[Reprints and e-prints](#)

[Advertising solutions](#)

[Accelerated publication](#)

[Corporate access solutions](#)

Open access

[Overview](#)

[Open journals](#)

[Open Select](#)

[Dove Medical Press](#)

[F1000Research](#)

Help and information

[Help and contact](#)

[Newsroom](#)

[All journals](#)

[Books](#)

Keep up to date

Register to receive personalised research and resources by email



Sign me up



Copyright © 2026 Informa UK Limited [Privacy policy](#)

[Cookies](#) [Terms & conditions](#) [Accessibility](#)

Registered in England & Wales No. 01072954
5 Howick Place | London | SW1P 1WG



Taylor & Francis
by informa