



Petroleum Science and Technology >

Volume 33, 2015 - [Issue 12](#)

967 | 75 | 0
Views | CrossRef citations to date | Altmetric

Original Articles

Effects of Nanoparticle Types on Carbon Dioxide Foam Flooding in Enhanced Oil Recovery

M. A. Manan, S. Farad, A. Piroozian  & M. J. A. Esmail

Pages 1286-1294 | Published online: 17 Aug 2015

 Cite this article  <https://doi.org/10.1080/10916466.2015.1057593>



Sample our
Economics, Finance,
Business & Industry Journals
>> **Sign in here** to start your access
to the latest two volumes for 14 days

 Full Article

 Figures & data

 References

 Citations

 Metrics

 Reprints & Permissions

Read this article

 Share

Abstract

Enhancement of foam stability has been recently evidenced with addition of nanoparticles (NPs), especially in the case of CO₂ foams. Stabilized foams via solid NPs can potentially withstand high reservoirs temperatures. Studies have been conducted to examine the effect of NPs on foam stability; however, more research is required for various types of NPs. Therefore, the authors aimed to investigate the performance of silicon dioxide (SiO₂), aluminum oxide (Al₂O₃), copper oxide (CuO), and titanium dioxide (TiO₂) of different sizes in the presence of fixed concentration of anionic surfactant (AOS) on foam stability. Nano particle concentrations of (0.1 wt%, 0.3 wt%, 0.5 wt%, and 1 wt%) were used to investigate the foam stability, displacement test were performed to determine oil recovery at the optimum concentrations for each nanoparticle. The stability of the aqueous foam was evaluated by the Ross-Miles

method using half-life measurements. All experiments were conducted at room temperature and pressure. The results revealed that all different NPs used were able to improve the stability of CO₂ foam at certain concentrations. However, aluminum oxide NPs showed better results compared to others in terms of foam stability and half-life time. In addition, 0.1 wt% of all NPs types gave the highest foam stability and half-life time. In conclusion, a low concentration of NPs is recommended regardless of type for improving form stability.

Keywords:

- foam stability
- nanoparticle
- enhanced oil recovery
- immiscible flooding
- surfactant

Related research 

People also read

Recommended articles

Cited by
75

Information for

[Authors](#)

[R&D professionals](#)

[Editors](#)

[Librarians](#)

[Societies](#)

Opportunities

[Reprints and e-prints](#)

[Advertising solutions](#)

[Accelerated publication](#)

[Corporate access solutions](#)

Open access

[Overview](#)

[Open journals](#)

[Open Select](#)

[Dove Medical Press](#)

[F1000Research](#)

Help and information

[Help and contact](#)

[Newsroom](#)

[All journals](#)

[Books](#)

Keep up to date

Register to receive personalised research and resources by email



Sign me up



Copyright © 2026 Informa UK Limited [Privacy policy](#) [Cookies](#) [Terms & conditions](#)

[Accessibility](#)

 Taylor and Francis Group

Registered in England & Wales No. 01072954
5 Howick Place | London | SW1P 1WG