 Open access

1,449 47




Views | CrossRef citations to date | Altmetric

0



Research Article

Algorithms for probabilistic uncertain linguistic multiple attribute group decision making based on the GRA and CRITIC method: application to location planning of electric vehicle charging stations

Guiwu Wei , Fan Lei, Rui Lin, Rui Wang, Yu Wei  , Jiang Wu  & ...show all

Pages 828-846 | Received 23 Aug 2019, Accepted 20 Feb 2020, Published online: 16 Mar 2020

 Download citation <https://doi.org/10.1080/1331677X.2020.1734851> Check for updates Full Article Figures & data References Supplemental Citations Metrics Licensing Reprints & Permissions View PDF View EPUB **Abstract**
SettingsFormulae display: **MathJax** 

Electric vehicles (EVs) could be regarded as one of the most innovative and high technologies all over the world to cope with the fossil fuel energy resource crisis and environmental pollution issues. As the initiatory task of EV charging station (EVCS) construction, site selection play an important part throughout the whole life cycle, which is deemed to be multiple attribute group decision making (MAGDM) problem involving many experts and many conflicting attributes. In this paper, a grey relational analysis (GRA) method is investigated to tackle the probabilistic uncertain linguistic MAGDM in which the attribute weights are completely unknown information.

(CRITIC) method. Then, the optimal alternative is chosen by calculating largest relative relational degree from the probabilistic uncertain linguistic positive ideal solution (PULPIS) which considers both the largest grey relational coefficient from the PULPIS and the smallest grey relational coefficient from the probabilistic uncertain linguistic negative ideal solution (PULNIS). Finally, a numerical case for site selection of electric vehicle charging stations (EVCS) is designed to illustrate the proposed method. The result shows the approach is simple, effective and easy to calculate.

Q Keywords: Multiple attribute group decision making (MAGDM)

probabilistic uncertain linguistic term sets (PULTSs)

grey relational analysis (GRA) method

CRITIC method

site selection

electric vehicle charging stations

Q JEL CODES: C43 C61 D81

1. Introduction

In many existing multiple attribute group decision making (MAGDM) issues, it has been assumed that almost all assessing information is expressed with crisp numbers (Pamucar & Cirovic, 2015). However, in more and more practical MAGDM issues, most of decision makers' (DMs') assessment information is imprecise or uncertain (H. Gao, Ran, Wei, Wei, & Wu, 2020; He, Wei, Lu, Wei, & Lin, 2019; L.P. Wu, Wei, Wu, & Wei, 2020) because of ever growing complexity and uncertainty of MAGDM issues and the fuzziness of human subjective preferences (X. M. Deng & Gao, 2019; H. Gao, Lu, & Wei, 2019; Li & Lu, 2019; J.P. Lu & Wei, 2019). In order to depict these qualitative assessment information easily (J. Wang, Gao, & Lu, 2019; R. Wang, 2019; L.P. Wu, Gao, & Wei, 2019; L.P. Wu, Wang, & Gao et al., 2019), Herrera and Martinez (2000) defined the linguistic term sets (LTSs) for computing with words. Furthermore, Rodriguez, Martinez, and Herrera (2012) proposed the hesitant fuzzy linguistic term sets (HFLTSS) on the basis of hesitant fuzzy sets (Torra, 2010) and linguistic term sets (LTSs) (Zadeh, 1975) which allowed DMs to provide some possible linguistic information. However, in most of the current references on HFLTSSs, all possible values are provided by the DMs have equal weight or importance. Thus, Pang, Wang, and Xu (2016) defined the probabilistic linguistic term sets (PLTSSs) to overcome this defect.

selection of new agricultural machinery products. Feng, Liu, and Wei (2019) proposed the probabilistic linguistic QUALitative FLEXible multiple criteria method (QUALIFLEX) method with possibility degree comparison. Chen, Wang, and Wang (2019) employed the probabilistic linguistic MULTIMOORA for cloud-based Enterprise Resource Planning (ERP) system selection. G.W. Wei, Wei, Wu, and Wang (2019) defined the supplier selection of medical consumption products with a probabilistic linguistic multi-attributive border approximation area comparison (MABAC) method. Lei, Wei, Lu, Wei, and Wu (2019) proposed the GRA method for probabilistic linguistic multiple attribute group decision making with incomplete weight information and its application to waste incineration plants location problem. Liao, Jiang, Lev, and Fujita (2019) studied the novel operations of PLTSs to solve the probabilistic linguistic ELimination Et Choix Traduisant la REalité (ELECTRE) III method. In some practical situations, a set of DMs may have their preferences to express their assessment information by using uncertain linguistic terms (Z.S. Xu, 2004) in the group decision making (GDM) processes because of lack of sufficient knowledge and the fuzziness of human's thinking. However, these uncertain linguistic terms are different from each other and also the number of occurrences of each uncertain linguistic term is different. Inspired by the idea based on probabilistic linguistic term sets (Pang et al., 2016) and uncertain linguistic term (Z.S. Xu, 2004), Lin, Xu, Zhai, and Yao (2018) designed a new concept of probabilistic uncertain linguistic term set in order to depict the uncertain linguistic information in the GDM issues. Xie, Ren, Xu, and Wang (2018) defined the probabilistic uncertain linguistic preference relation (PULPR) and the normalized PULPR and designed the distance measure and similarity degree measure the consensus degree. Y. He, Lei, et al. (2019) defined the EDAS method for multiple attribute group decision making with probabilistic uncertain linguistic information and its application to green supplier selection.

The grey relational analysis (GRA) method was firstly developed by J. L. Deng (1989) to solve the MADM issue, which concentrates on selecting the alternative with the largest grey relational degree from the PIS and with the smallest grey relational degree from the NIS. Kuo, Yang, and Huang (2008) utilized GRA method to solve the MADM issues for facility layout and dispatching rules selection. Kung and Wen (2007) used six financial indicators to classify twenty items of financial ratios by GRA method to arrange the total performances of the sample venture capital enterprises in order.

studied the green design alternatives and GRA integrated with Analytical Hierarchy Process (AHP). Sun, Guan, Yi, and Zhou (2018) and HFSs slope grey relational degree together to construct the HFSs synthetic grey relational degree which takes both the closeness and the linear fashion into consideration. Malek, Ebrahimnejad, and Tavakkoli-Moghaddam (2017) proposed an improved hybrid GRA method for green resilient supply. G. D. Tian et al. (2018) defined the grey-correlation based hybrid multi-criteria decision making (MCDM) method for green decoration materials selection under interior environment characteristics. G. Tian et al. (2019) designed the fuzzy grey Choquet integral for evaluation of multicriteria decision making problems with interactive and qualitative indices.

But there are no studies on the GRA method for MAGDM under PULTSs in the existing literature. Therefore, it is necessary to pay attention to this issue. The goal of this paper is to extend the GRA method to solve the probabilistic uncertain linguistic MAGDM with unknown weight information on the basis of the CRITIC method. The motivation of such paper can be outlined as follows: (1) the GRA method is extended by PULTSs with unknown weight information; (2) the scoring function of PULTs is employed to objectively derive the attribute weights based on the CRITIC method; (3) the probabilistic uncertain linguistic GRA (PUL-GRA) method is proposed to solve the probabilistic uncertain linguistic MAGDM problems; (4) a case study for site selection of EVCS is supplied to show the developed approach; (5) some comparative studies are provided with the PULWA operator, ULWA operator and PUL-TOPSIS method to give effect to the rationality of PUL-GRA method.

The remainder of this paper is organized as follows. [Section 2](#) supplies some basic concepts of PULTSs. In Sect. 3, the probabilistic uncertain linguistic GRA method is proposed for MAGDM issue with CRITIC-based weight information. In Sect. 4, a case study for site selection of EVCS is given and some comparative analysis is conducted. The study ends with some conclusions in Sect. 5.

2. Preliminaries

terms and $[0,1]$.

Definition 1.

(Gou et al., 2017; Z. S. Xu, 2005). Let $L = \{l_\alpha | \alpha = -\theta, \dots, -2, -1, 0, 1, 2, \dots, \theta\}$ be an LTS (Z. S. Xu, 2005), the linguistic terms l_α can depict the equivalent information to β is obtained by the transformation function g (Gou et al., 2017):

$$g: [l_{-\theta}, l_\theta] \rightarrow [0, 1], g(l_\alpha) = \frac{\alpha + \theta}{2\theta} = \beta \quad (1)$$

At the same time, β can be expressed the equivalent information to the linguistic terms l_α , which is derived by the transformation function g^{-1} :

$$g^{-1}: [0, 1] \rightarrow [l_{-\theta}, l_\theta], g^{-1}(\beta) = l_{(2\beta - 1)\theta} = l_\alpha \quad (2)$$

In order to strengthen the modeling capability of HFLTSSs, Pang et al. (2016) designed the definition of PLTSs to link each linguistic term with a probability value.

Definition 2.

(Pang, et al., 2016). Given an LTS $L = \{l_j | j = -\theta, \dots, -2, -1, 0, 1, 2, \dots, \theta\}$, a PLTS is designed as:

$$L(p) = \{l(\phi)(p(\phi)) | l(\phi) \in L, p(\phi) \geq 0, \phi = 1, 2, \dots, \#L(p), \sum_{\phi=1}^{\#L(p)} p(\phi) \leq 1\} \quad (3)$$

where $l(\phi)(p(\phi))$ is the ϕ th linguistic term $l(\phi)$ associated with the probability value $p(\phi)$, and $\#L(p)$ is the length of linguistic terms in $L(p)$. The linguistic term $l(\phi)$ in $L(p)$ are arranged in ascending order.

In order to express the DMs' uncertainty more accurately, Lin et al. (2018) came forward the probabilistic uncertain linguistic term sets (PULTS) based on uncertain linguistic term (Z.S. Xu, 2004) and probabilistic linguistic term sets

Definition 3.

(Lin et al., 2018). A PULTS could be designed as follows:

(4)

where $[L_\phi, U_\phi](p_\phi)$ depicts the uncertain linguistic term $[L_\phi, U_\phi]$ associated with the probability p_ϕ , L_ϕ, U_ϕ are linguistic term sets, $L_\phi \leq U_\phi$, and $\#PULTS(p)$ is the cardinality of $PULTS(p)$.

In order to convenient computation, Lin et al. (2018) normalized the PULTS $PULTS(p)$ as $NPULTS(p) = \{[L_{\tilde{\phi}}, U_{\tilde{\phi}}](p_{\tilde{\phi}}) | p_{\tilde{\phi}} \geq 0, \tilde{\phi} = 1, 2, \dots, \#NPULTS(p), \sum_{\tilde{\phi}=1}^{\#NPULTS(p)} p_{\tilde{\phi}} = 1\}$, where $p_{\tilde{\phi}} = p(\phi) / \sum_{\phi=1}^{\#L(p)} p(\phi)$ for all $\tilde{\phi} = 1, 2, \dots, \#NPULTS(p)$.

Definition 4.

(Lin et al., 2018). Let $PULTS_1(p) = \{[L_{1\phi}, U_{1\phi}](p_{1\phi}) | \phi = 1, 2, \dots, \#PULTS_1(p)\}$ and $PULTS_2(p) = \{[L_{2\phi}, U_{2\phi}](p_{2\phi}) | \phi = 1, 2, \dots, \#PULTS_2(p)\}$ be two PULTSs, where $\#PULTS_1(p)$ and $\#PULTS_2(p)$ are the numbers of PULTSs $PULTS_1(p)$ and $PULTS_2(p)$, respectively. If $\#PULTS_1(p) > \#PULTS_2(p)$, then add $\#PULTS_1(p) - \#PULTS_2(p)$ linguistic terms to $PULTS_2(p)$. Moreover, the added uncertain linguistic terms should be the smallest linguistic term in $PULTS_2(p)$ and the probabilities of added linguistic terms should be zero.

Definition 5.

(Lin et al., 2018). For the $PULTS(p) = \{[L_\phi, U_\phi](p_\phi) | \phi = 1, 2, \dots, \#PULTS(p)\}$, the expected value $E(PULTS(p))$ and deviation degree $DD(PULTS(p))$ of $PULTS(p)$ is defined:

$$EV(PULTS(p)) = \sum_{\phi=1}^{\#PULTS(p)} (g(L_\phi)p_\phi + g(U_\phi)p_\phi) / \sum_{\phi=1}^{\#PULTS(p)} p_\phi$$

(5)

$$DD(PULTS(p)) = \sum_{\phi=1}^{\#PULTS(p)} (g(L_\phi)p_\phi + g(U_\phi)p_\phi - E(PULTS(p)))^2 / \sum_{\phi=1}^{\#PULTS(p)} p_\phi$$

(6)

By using the Eqs (4)-(5), the order relation between two PULTSs is defined as: (1) if $EV(PULTS_1(p)) > EV(PULTS_2(p))$, then $PULTS_1(p) > PULTS_2(p)$; (2) if $EV(PULTS_1(p)) = EV(PULTS_2(p))$, then if $DD(PULTS_1(p)) = DD(PULTS_1(p))$, then $PULTS_1(p) = PULTS_2(p)$; if $DD(PULTS_1(p)) < DD(PULTS_1(p))$, then, $PULTS_1(p) > PULTS_2(p)$.

Definition 6.

$\#PULTS1(p)=\#PULTS2(p)=\#PULTS(p)$, then Hamming distance $HD(PULTS1(p), PULTS2(p))$ between $PULTS1(p)$ and $PULTS2(p)$ is defined as follows:

$$HD(PULTS1(p),PULTS2(p))=\sum_{\phi=1}^{\#PULTS(p)} (|g(L1\phi)p\phi-g(L2\phi)p\phi|+|g(U1\phi)p\phi-g(U2\phi)p\phi|)2\#PULTS(p)$$

(7)

3. GRA method for PUL-MAGDM with CRITIC weight

In such section, we propose the probabilistic uncertain linguistic GRA (PUL-GRA) method for MAGDM problems with unknown weight information. The following mathematical notations are used to denote the probabilistic linguistic MAGDM problems. Let $A=\{A1,A2,\dots,Am\}$ be a discrete set of chosen alternatives, and $G=\{G1,G2,\dots,Gn\}$ with weight vector $w=(w1,w2,\dots,wn)$, where $wj\in[0,1]$, $j=1,2,\dots,n$, $\sum_{j=1}^n wj=1$, and a set of experts $E=\{E1,E2,\dots,Eq\}$. Suppose that there are n qualitative attribute and their values are evaluated by qualified experts and denoted as uncertain linguistic expressions information $[Lijk,Uijk](i=1,2,\dots,m,j=1,2,\dots,n,k=1,2,\dots,q)$.

Then, PUL-GRA method is designed to solve the MAGDM problems with PULTs and CRITIC weight. The detailed calculating steps are listed as follows:

Step 1. Shift cost attribute into beneficial attribute. If the cost attribute value is $[\alpha,\beta]$, then the corresponding beneficial attribute value is $[1-\beta,1-\alpha]$.

Step 2. Convert the uncertain linguistic information $[Lijk,Uijk](i=1,2,\dots,m,j=1,2,\dots,n,k=1,2,\dots,q)$ into probabilistic uncertain linguistic decision matrix $PULDM=(PULDMij(p))m\times n$, $PULDMij(p)=\{[Lij\phi,Uij\phi](pij\phi)|\phi=1,2,\dots,\#PULDMij(p)\}(i=1,2,\dots,m,j=1,2,\dots,n)$.

Step 3. Obtain the normalized probabilistic uncertain linguistic matrix $NPULDM=(NPULDMij(p))m\times n$, $NPULDMij(p)=\{[Lij\phi,Uij\phi](pij\phi)|\phi=1,2,\dots,\#NPULDMij(p)\}(i=1,2,\dots,m,j=1,2,\dots,n)$. Thus, probabilistic uncertain linguistic information for the

Step 4. Compute the weight values by CRITIC method.

In such section, an essential method called CRiteria Importance Through Intercriteria Correlation (CRITIC) was initially presented by (Diakoulaki., Mavrotas., & Papayannakis., 1995), will be introduced to decide the objective weights of attributes. Subsequently, the detailed computing procedures of this combined weight method are given as follows.

1. Build the probabilistic uncertain linguistic correlation coefficient matrix $PULCCM=(PULCC_{jt})_{n \times n}$ by computing the correlation coefficient between attributes.

$$PULCC_{jt} = \frac{\sum_{i=1}^m ((\sum_{\phi=1}^{\#NPULDM_{ij}(p)} (g(L_{ij\phi})p_{ij\phi} - g(L_{j\phi})p_{j\phi}) + (g(U_{ij\phi})p_{ij\phi} - g(U_{j\phi})p_{j\phi})^2) \cdot (\sum_{\phi=1}^{\#NPULDM_{ij}(p)} (g(L_{it\phi})p_{it\phi} - g(L_{t\phi})p_{t\phi}) + (g(U_{it\phi})p_{it\phi} - g(U_{t\phi})p_{t\phi})^2))}{\sum_{i=1}^m (\sum_{\phi=1}^{\#NPULDM_{ij}(p)} (g(L_{ij\phi})p_{ij\phi} - g(L_{j\phi})p_{j\phi}) + (g(U_{ij\phi})p_{ij\phi} - g(U_{j\phi})p_{j\phi})^2) \cdot \sum_{i=1}^m ((\sum_{\phi=1}^{\#NPULDM_{ij}(p)} (g(L_{it\phi})p_{it\phi} - g(L_{t\phi})p_{t\phi}) + (g(U_{it\phi})p_{it\phi} - g(U_{t\phi})p_{t\phi})^2))}^2},$$

$$j, t = 1, 2, \dots, n$$

(7)

where $[L_{j\phi}, U_{j\phi}](p_{j\phi}) = [\sum_{i=1}^m L_{ij\phi}m, \sum_{i=1}^m U_{ij\phi}m] / (\sum_{i=1}^m p_{ij\phi}m)$ and $[L_{t\phi}, U_{t\phi}](p_{t\phi}) = [\sum_{i=1}^m L_{it\phi}m, \sum_{i=1}^m U_{it\phi}m] / (\sum_{i=1}^m p_{it\phi}m)$.

2. Derive the probabilistic uncertain linguistic standard deviation (PULSD) of attribute.

$$PULSD_j = \frac{1}{m-1} \sum_{i=1}^m (\sum_{\phi=1}^{\#NPULDM_{ij}(p)} (g(L_{ij\phi})p_{ij\phi} - g(L_{j\phi})p_{j\phi}) + (g(U_{ij\phi})p_{ij\phi} - g(U_{j\phi})p_{j\phi})^2)^2},$$

$$j = 1, 2, \dots, n,$$

(8)

3. Compute the objective weights of attributes.

$$w_j = \frac{PULSD_j \sum_{t=1}^n (1 - PULCC_{jt})}{\sum_{j=1}^n (PULSD_j \sum_{t=1}^n (1 - PULCC_{jt}))}, j = 1, 2, \dots, n,$$

Step 5. Define the probabilistic linguistic positive ideal solution (PLPIS) and probabilistic linguistic negative ideal solution (PLNIS):

$$(10) \quad \text{PULPIS} = (\text{PULPIS}_1, \text{PULPIS}_2, \dots, \text{PULPIS}_n)$$

$$(11) \quad \text{PULNIS} = (\text{PULNIS}_1, \text{PULNIS}_2, \dots, \text{PULNIS}_n)$$

where

$$(12) \quad \text{PULPIS}_j = \{p_{lj\phi}(p_{j\phi}) \mid \phi = 1, 2, \dots, \# \text{NPULDM}_{ij}(p)\}, \text{EV}(\text{PULPIS}_j) = \{\max_i \text{EV}(\text{NPULDM}_{ij}(p))\}$$

$$(13) \quad \text{PULNIS}_j = \{n_{lj\phi}(p_{j\phi}) \mid \phi = 1, 2, \dots, \# \text{NPULDM}_{ij}(p)\}, \text{EV}(\text{PULNIS}_j) = \{\min_i \text{EV}(\text{NPULDM}_{ij}(p))\}$$

Step 6. Calculate the grey relational coefficient of each alternative from PULPIS and PULNIS, respectively:

The grey relational coefficient of each alternative from PULPIS is given as

$$\text{PULPIS}(\xi_{ij}) = \frac{\min_{1 \leq i \leq m} \min_{1 \leq j \leq n} \text{HD}(\text{PULAI}_{ij}, \text{PULPIS}_j) + \rho \max_{1 \leq i \leq m} \max_{1 \leq j \leq n} \text{HD}(\text{PULAI}_{ij}, \text{PULPIS}_j)}{\text{HD}(\text{PULAI}_{ij}, \text{PULPIS}_j) + \rho \max_{1 \leq i \leq m} \max_{1 \leq j \leq n} \text{HD}(\text{PULAI}_{ij}, \text{PULPIS}_j)},$$

$$i = 1, 2, \dots, m, j \in 1, 2, \dots, n.$$

(14)

Similarly, the grey relational coefficient of each alternative from PULNIS is given as

$$\text{PULNIS}(\xi_{ij}) = \frac{\min_{1 \leq i \leq m} \min_{1 \leq j \leq n} \text{HD}(\text{PULAI}_{ij}, \text{PULNIS}_j) + \rho \max_{1 \leq i \leq m} \max_{1 \leq j \leq n} \text{HD}(\text{PULAI}_{ij}, \text{PULNIS}_j)}{\text{HD}(\text{PULAI}_{ij}, \text{PULNIS}_j) + \rho \max_{1 \leq i \leq m} \max_{1 \leq j \leq n} \text{HD}(\text{PULAI}_{ij}, \text{PULNIS}_j)},$$

$$i = 1, 2, \dots, m, j \in 1, 2, \dots, n.$$

$$HD(PULA_{ij}, PULPIS_j) = (\sum_{\phi=1}^{\#NPULDM_{ij}(p)} |p_{ij\phi}g(L_{ij\phi}) - p_j\phi g(L_j\phi)| + |p_{ij\phi}g(U_{ij\phi}) - p_j\phi g(U_j\phi)|) / 2 \#NPULDM_{ij}(p)$$

(16)

Step 7. Calculating the degree of grey relational coefficient of each alternative from PULPIS and PULNIS by using the following equation, respectively:

$$PULPIS(\xi_i) = \sum_{j=1}^n w_j PULPIS(\xi_{ij}), i=1, 2, \dots, m,$$

(18)

$$PULNIS(\xi_i) = \sum_{j=1}^n w_j PULNIS(\xi_{ij}), i=1, 2, \dots, m,$$

(19)

The fundamental principle of the GRA method is that the chosen alternative should have the 'largest degree of grey relational coefficient' from the PULPIS and the 'smallest degree of grey relational coefficient' from the PULNIS. Obviously, the larger $PULPIS(\xi_i)$ and the smaller $PULNIS(\xi_i)$, the better alternative A_i is.

Step 8. Calculate the probabilistic uncertain linguistic relative relational degree (PULRRD) of each alternative from PULPIS.

$$PULRRD(\xi_i) = PULPIS(\xi_i) / (PULPIS(\xi_i) + PULNIS(\xi_i)), i=1, 2, \dots, m,$$

(20)

Step 9. According to $PULRRD(\xi_i)$, the ranking order of all alternatives can be determined. Thus, if any alternative has the largest $PULRRD(\xi_i)$ value, then, it is the optimal alternative.

4. A case study and comparative analysis

4.1. A case study

Along with the convenience of transportation, motor vehicle becomes the primary source of pollution. The issues of energy and environment pollution attract high

national strategy. As the representative of new energy vehicles, electric vehicles with low energy consumption and zero pollution have been developed rapidly. Therefore, it is imperative to promote electric logistics vehicles in the logistics industry. The use of electric logistics vehicle distribution can not only reduce harmful gas emissions, but also reduce logistics costs. At present, the problem of difficult charging seriously restricts the large-scale operation of electric logistics vehicles. Perfect charging facilities are an important guarantee to promote the large-scale use of electric logistics vehicles, and it is particularly important to reasonably determine the location distribution of charging facilities. At the same time, compared with the distribution of traditional fuel vehicles, the distribution of electric logistics vehicles is faced with difficulties such as limited battery capacity, few charging facilities and long charging time, so the traditional vehicle route distribution method cannot be directly applied to the distribution system of electric logistics vehicles. The location of charging station and the path planning of electric logistics vehicle depend on each other, so it is necessary to combine the site selection and vehicle path planning. The site selection of EVCS is deemed as a kind of MAGDM issue(Li et al., 2019; J. Wang, Lu, Wei, Lin, & Wei, 2019; J. Wang, Wei, et al., 2019; G. W. Wei, Wang, Wei, Wei, & Zhang, 2019; S. Q. Zhang, Wei, Gao, Wei, & Wei, 2019). Thus, in this section we present a numerical example for site selection of EVCS to illustrate the method designed in this paper. There are five possible EVCS sites $A_i(i=1,2,3,4,5)$ to select. The experts selects four attribute to evaluate the five possible EVCS sites: ① G_1 is the waste discharge; ② G_2 is the construction cost; ③ G_3 is the traffic convenience; ④ G_4 is the service capability. The construction cost is not beneficial attribute, others are beneficial attribute. The five possible EVCS sites $A_i(i=1,2,3,4,5)$ are to be evaluated by using the linguistic term set

$$L =$$

$$\{l_{-3} = \text{extremely poor (EP)}, l_{-2} = \text{very poor (VP)}, l_{-1} = \text{poor (P)}, l_0 = \text{medium (M)}, l_1 = \text{good (G)}, l_2 = \text{very good (VG)}, l_3 = \text{extremely good (EG)}\}$$

by the five decision makers under the above four attributes, as listed in the [Tables 1-5](#).

Table 1. Uncertain linguistic assessing matrix by the DM_1 .

Table 2. Uncertain linguistic assessing matrix by the DM_2 .

[Download CSV](#)

[Display Table](#)



Table 3. Uncertain linguistic assessing matrix by the DM_3 .

[Download CSV](#)

[Display Table](#)




Table 4. Uncertain linguistic assessing matrix by the DM_4 .

[Download CSV](#)

[Display Table](#)



Table 5. Uncertain linguistic assessing matrix by the DM_5 .

[Download CSV](#)

[Display Table](#)



Table 6. Uncertain linguistic assessing matrix by the DM_1 .

[Download CSV](#)

[Display Table](#)




Table 7. Uncertain linguistic assessing matrix by the DM_2 .

[Download CSV](#)

[Display Table](#)



Table 8. Uncertain linguistic assessing matrix by the DM₃.

[Download CSV](#)

[Display Table](#)



Table 9. Uncertain linguistic assessing matrix by the DM₄.

[Download CSV](#)

[Display Table](#)



Table 10. Uncertain linguistic assessing matrix by the DM₅.

[Download CSV](#)

[Display Table](#)



Table 11. Probabilistic uncertain linguistic assessing matrix.

[Display Table](#)



Table 12. Normalized probabilistic uncertain linguistic assessing matrix.

[Display Table](#)



Table 13. PULPIS and PULNIS.

[Display Table](#)



Table 14. GRC of each alternative from PULPIS.

Table 14. PULPIS(ξ_i) and PULNIS(ξ_i) of each alternative.

[Display Table](#)



Table 15. GRC of each alternative from PULNIS.

[Download CSV](#)

[Display Table](#)



Table 15. PULRRD of each alternative from PULPIS.

[Display Table](#)



Table 16. The sensitively analysis for PUL-GRA method.

[Display Table](#)



Table 17. The calculating results and sorting results by using PUL-TOPSIS method.

[Display Table](#)



Table 18. Group uncertain linguistic decision matrix.

[Display Table](#)



Step 1. Shift cost attribute G_2 into beneficial attribute. If the cost attribute value is $[\alpha, \beta] (-3 \leq \alpha, \beta \leq 3)$, then the corresponding beneficial attribute value is $[s - \beta, s - \alpha]$ (See [Tables 6–10](#)).

Step 2. Transform the uncertain linguistic variables into probabilistic uncertain linguistic assessing matrix ([Table 11](#)).

Step 3. Calculate the normalized probabilistic uncertain linguistic assessing matrix ([Table 12](#)).

Step 4. Define the probabilistic linguistic positive ideal solution (PLPIS) and probabilistic linguistic negative ideal solution (PLNIS) ([Table 13](#)).

Step 5. Computing the corresponding GRC of each alternative from PULPIS and PULNIS ([Tables 14 and 15](#)), let $\rho = 0.5$:

Step 6. the weight vector of attributes can be got: $w = (0.2966, 0.1930, 0.2534, 0.2570)^T$.

Step 7. Calculating the degree of GRC of all possible alternatives from PULPIS and PULNIS, respectively ([Table 14](#)):

Step 8. Calculating the PULRRD(ξ_i) of each alternative from PULPIS by Eq.(14) ([Table 15](#)).

Step 9. According to the PULRRD(ξ_i)($i=1,2,3,4,5$), all the waste incineration plants sites can be ranked. Evidently, the order is $A_3 > A_4 > A_5 > A_1 > A_2$ and the most desirable EVCS site among five alternatives is A_3 .

At the same time, we conduct the sensitively analysis to show the robustness of the proposed method. The parameter value ρ varies from 0.1 to 1. We could get the calculating result which is listed in [Table 16](#). The ranking result is same and the order is: $A_3 > A_4 > A_5 > A_1 > A_2$ when The parameter value ρ varies from 0.1 to 1. The optimal alternative is still is A_3 and the worst alternative is A_2 . It could be seen that the proposed PUL-GRA method is robust and effective.

4.2. Comparative analysis

(Lin et al., 2018) and ULWA operator (Z.S. Xu, 2004).

4.2.1. Compared with PULWA operator

Firstly, we compare our proposed method with probabilistic uncertain linguistic weighted average (PULWA) operator (Lin et al., 2018), the weight vector of attributes is derived as: $w_1=0.2996, w_2=0.1930, w_3=0.2534, w_4=0.2570$, then the overall attribute value of each alternative $Z_i(w)(i=1,2,3,4,5)$ is obtained by employing PULWA operator.

$$Z_1(w) = \{[-0.9656, -0.5535], [-0.3925, -0.1286], [-0.0613, 0.2626]\}$$

$$Z_2(w) = \{[-0.6497, -0.4331], [-0.5042, -0.2521], [-1.0382, -0.5069]\}$$

$$Z_3(w) = \{[0.0000, 0.0514], [0.2121, 0.4242], [1.4730, 2.2095]\}$$

$$Z_4(w) = \{[0.0000, 0.1158], [-0.0452, 0.2655], [0.6131, 1.1866]\}$$

$$Z_5(w) = \{[-0.1414, 0.2707], [0.1693, 0.5572], [0.3100, 0.5100]\}$$

Then, the score values of these five overall attribute values of each alternative $Z_i(w)$ ($i=1,2,3,4,5$) are obtained by Definition 9 (Lin et al., 2018) as follows:

$$E(Z_1(w)) = -0.2043, E(Z_2(w)) = -0.3760, E(Z_3(w)) = 0.4856, E(Z_4(w)) = 0.2373, E(Z_5(w)) = 0.1862$$

Furthermore, we can derive the ranking result: $A_3 > A_4 > A_5 > A_1 > A_2$. Thus, we have the same optimal EVCS site A_3 .

4.2.2. Compared with PUL-TOPSIS method

Then, we compare our proposed method with probabilistic uncertain linguistic TOPSIS method (PUL-TOPSIS method) (Lin et al., 2018), then we can acquire the calculating results and sorting results (Table 17). Thus, we have the same optimal EVCS site A_2 .

4.2.3. Compared with ULWA operator

information to fuse all the uncertain linguistic decision matrices provided by the DMs into a group uncertain linguistic decision matrix (See [Table 18](#)).

The attributes weight is derived as: $w_1=0.2800, w_2=0.3200, w_3=0.1100, w_4=0.2900$, then the overall values of these five alternatives $Z_i(w)(i=1,2,3,4,5)$ is obtained by using ULWA operator (Z.S. Xu, [2004](#)).

$$Z_1(w)=[l-1.4194, l-0.4194], Z_2(w)=[l-2.1921, l-1.1921], Z_3(w)=[l1.6851, l2.6851]$$

$$Z_4(w)=[l0.5679, l1.5679], Z_5(w)=[l0.3379, l1.3379]$$

Then, the score values of these five alternatives $Z_i(w)(i=1,2,3,4,5)$ are obtained by Definition 9 (Lin et al., [2018](#)) as follows:

$$E(Z_1(w))=l-0.9194, E(Z_2(w))=l-1.6921, E(Z_3(w))=l2.1851$$

$$E(Z_4(w))=l1.0679, E(Z_5(w))=l0.8379$$

Furthermore, we can derive the ranking result: $A_3 > A_4 > A_5 > A_1 > A_2$. Thus, we have the same optimal EVCS site A_3 .

5. Conclusion

In this paper, we extend the classical GRA method to the probabilistic uncertain linguistic MAGDM with unknown weight information. Firstly, the basic concept, comparative formula and Hamming distance of PULTs are briefly introduced. Then, the definition of the expected value is employed to objectively compute the attribute weights based on the CRITIC method. Then, the optimal alternative(s) is determined by calculating the 'largest degree of grey relational coefficient' from the PULPIS and the 'smallest degree of grey relational coefficient' from the PULNIS. Finally, a practical case study for site selection of EVCS is provided to validate the proposed algorithm and some comparative analysis is also designed to verify the applicability. In the future, the application of the proposed models and methods with PULTSs needs to be investigated into other practical applicable domains (Stanujkic, Karabasevic,

Saparauskas, & Turskis, 2013) and uncertain and fuzzy cognitive environments (Dahooie et al., 2019; Jahan & Zavadskas, 2019; G. Tian et al., 2017; J. Wang, Gao, & Wei, 2019; G. W. Wei, Wang, Wang, et al., 2019; G.W. Wei, Wu, Wei, Wang, & Lu et al., 2019; K. Zhang et al., 2018). At the same time, we shall continue to investigate the PUL-MAGDM with incomplete weight information.

Related Research Data

[A 2-tuple fuzzy linguistic representation model for computing with words](#)

Source: Institute of Electrical and Electronics Engineers (IEEE)

[A Bipolar Fuzzy Extension of the MULTIMOORA Method](#)

Source: Vilniaus universiteto Matematikos ir informatikos institutas; Lietuvos Mokslų akademija

[An Improved Hybrid Grey Relational Analysis Approach for Green Resilient Supply Chain Network Assessment](#)

Source: MDPI AG

[An improved fuzzy MULTIMOORA approach for multi-criteria decision making based on objective weighting method \(CCSD\) and its application to technological forecasting method selection](#)

Source: Elsevier BV

[Applying Grey Relational Analysis and Grey Decision-Making to evaluate the relationship between company attributes and its financial performance-A case study of venture capital enterprises in Taiwan](#)

Source: Elsevier BV

[Approaches to strategic supplier selection under interval neutrosophic environment](#)

Source: IOS Press

entropy and dynamic VIKOR

Source: Institute of Electrical and Electronics Engineers (IEEE)

Cloud-based ERP system selection based on extended probabilistic linguistic MULTIMOORA method and Choquet integral operator

Source: Springer Science and Business Media LLC

Determining objective weights in multiple criteria problems: the critic method

Source: Elsevier BV

Deviation measures of linguistic preference relations in group decision making

Source: Elsevier BV

Dual Hesitant Pythagorean Fuzzy Hamy Mean Operators in Multiple Attribute Decision Making

Source: Institute of Electrical and Electronics Engineers (IEEE)

Dual hesitant bipolar fuzzy hamacher aggregation operators and their applications to multiple attribute decision making

Source: IOS Press

EDAS METHOD FOR MULTIPLE ATTRIBUTE GROUP DECISION MAKING UNDER Q-RUNG ORTHOPAIR FUZZY ENVIRONMENT

Source: Vilnius Gediminas Technical University

EDAS METHOD FOR MULTIPLE CRITERIA GROUP DECISION MAKING WITH PICTURE FUZZY INFORMATION AND ITS APPLICATION TO GREEN SUPPLIERS SELECTIONS

Source: VGTU Press TECHNIKA

ELECTRE-IDAT for design decision-making problems with interval data and target-based criteria

Source: Springer Science and Business Media LLC

Source: Institute of Electrical and Electronics Engineers (IEEE)

Green decoration materials selection under interior environment characteristics:
A grey-correlation based hybrid MCDM method

Source: Elsevier BV

Grey relational analysis between hesitant fuzzy sets with applications to pattern recognition

Source: Elsevier BV

Hesitant Fuzzy Linguistic Term Sets for Decision Making

Source: Institute of Electrical and Electronics Engineers (IEEE)

Hesitant fuzzy sets

Source: Wiley

Methods for Evaluating the Technological Innovation Capability for the High-Tech Enterprises With Generalized Interval Neutrosophic Number Bonferroni Mean Operators

Source: Institute of Electrical and Electronics Engineers (IEEE)

Models for MADM With 2-Tuple Linguistic Neutrosophic Dombi Bonferroni Mean Operators

Source: Institute of Electrical and Electronics Engineers (IEEE)

Models for MADM with Single-Valued Neutrosophic 2-Tuple Linguistic Muirhead Mean Operators

Source: MDPI AG

Models for competitiveness evaluation of tourist destination with some interval-valued intuitionistic fuzzy Hamy mean operators

Source: IOS Press

Source: Informa UK Limited

Multiple criteria decision making based on Bonferroni means with hesitant fuzzy linguistic information

Source: Springer Science and Business Media LLC

Novel operations of PLTSs based on the disparity degrees of linguistic terms and their use in designing the probabilistic linguistic ELECTRE III method

Source: Elsevier BV

Operation patterns analysis of automotive components remanufacturing industry development in China

Source: Elsevier BV

Probabilistic linguistic QUALIFLEX approach with possibility degree comparison

Source: IOS Press

Probabilistic linguistic term sets in multi-attribute group decision making

Source: Elsevier BV

Pythagorean 2-Tuple Linguistic Taxonomy Method for Supplier Selection in Medical Instrument Industries.

Source: MDPI AG

Research on the application of the financial investment risk appraisal models with some interval number muirhead mean operators

Source: IOS Press

Some novel similarity and distance measures of pythagorean fuzzy sets and their applications

Source: IOS Press

Some q-rung orthopair fuzzy Hamy mean operators in multiple attribute decision-making and their application to enterprise resource planning systems

Supplier Selection of Medical Consumption Products with a Probabilistic Linguistic MABAC Method.

Source: MDPI AG

TODIM method for multiple attribute decision making with 2-tuple linguistic pythagorean fuzzy information

Source: IOS Press

TODIM method for performance appraisal on social-integration-based rural reconstruction with interval-valued intuitionistic fuzzy information

Source: IOS Press

The concept of a linguistic variable and its application to approximate reasoning —II

Source: Elsevier BV

The consensus of probabilistic uncertain linguistic preference relations and the application on the virtual reality industry

Source: Elsevier BV

The generalized Dice similarity measures for Pythagorean fuzzy multiple attribute group decision making

Source: Wiley

The generalized dice similarity measures for multiple attribute decision making with hesitant fuzzy linguistic information

Source: Informa UK Limited

The selection of transport and handling resources in logistics centers using Multi-Attributive Border Approximation area Comparison (MABAC)

Source: Elsevier BV

Source: Elsevier BV

Uncertain linguistic aggregation operators based approach to multiple attribute group decision making under uncertain linguistic environment

Source: Elsevier BV

VIKOR Method for MAGDM Based on Q-Rung Interval-Valued Orthopair Fuzzy Information and Its Application to Supplier Selection of Medical Consumption Products.

Source: Multidisciplinary Digital Publishing Institute

VIKOR method for financing risk assessment of rural tourism projects under interval-valued intuitionistic fuzzy environment

Source: IOS Press

selection of carpenter manufacturer using fuzzy EDAS method

Source: Inžinerinė ekonomika = Engineering economics

Linking provided by  ScholarSplorer

Disclosure statement

No potential conflict of interest was reported by the author(s).

Additional information

Funding

The work was supported by the National Natural Science Foundation of China under Grant No. 71571128 and the Humanities and Social Sciences Foundation of Ministry of Education of the People's Republic of China (No. 14XJCZH002).

References

1. Alptekin, O., Alptekin, N., & Sarac, B. (2018). Evaluation of Low Carbon Development of European Union Countries and Turkey Using Grey Relational Analysis. *Tehnicki Vjesnik-Technical Gazette*, 25, 1497–1505. [[Web of Science ®](#)], [[Google Scholar](#)]
2. Chen, S. X., Wang, J. Q., & Wang, T. L. (2019). Cloud-based ERP system selection based on extended probabilistic linguistic MULTIMOORA method and Choquet integral operator. *Computational & Applied Mathematics*, 38, 88. [[Crossref](#)], [[Web of Science ®](#)], [[Google Scholar](#)]
3. Dahooie, J. H., Zavadskas, E. K., Firoozfar, H. R., Vanaki, A. S., Mohammadi, N., & Brauers, W. K. M. (2019). An improved fuzzy MULTIMOORA approach for multi-criteria decision making based on objective weighting method (CCSD) and its application to technological forecasting method selection. *Engineering Applications of Artificial Intelligence*, 79, 114–128. doi:10.1016/j.engappai.2018.12.008 [[Crossref](#)], [[Web of Science ®](#)], [[Google Scholar](#)]
4. Deng, J. L. (1989). Introduction to Grey System. *The Journal of Grey System*, 1, 1–24. [[Google Scholar](#)]
5. Deng, X. M., & Gao, H. (2019). TODIM method for multiple attribute decision making with 2-tuple linguistic Pythagorean fuzzy information. *Journal of Intelligent & Fuzzy Systems*, 37, 1769–1780. doi:10.3233/JIFS-179240 [[Crossref](#)], [[Web of Science ®](#)], [[Google Scholar](#)]
6. Diakoulaki, D., Mavrotas, G., & Papayannakis, L. (1995). Determining objective weights in multiple criteria problems: The critic method. *Computers & Operations Research*, 22, 763–770. doi:10.1016/0305-0548(94)00059-H [[Crossref](#)], [[Web of Science ®](#)], [[Google Scholar](#)]

730. doi:10.3233/JIFS-172112 [[Crossref](#)], [[Web of Science ®](#)], [[Google Scholar](#)]
8. Gao, H., Lu, M., & Wei, Y. (2019). Dual hesitant bipolar fuzzy hamacher aggregation operators and their applications to multiple attribute decision making. *Journal of Intelligent & Fuzzy Systems*, 37, 5755–5766. doi:10.3233/JIFS-18266 [[Crossref](#)], [[Web of Science ®](#)], [[Google Scholar](#)]
9. Gao, H., Ran, L. G., Wei, G. W., Wei, C., & Wu, J. (2020). VIKOR Method for MAGDM Based on Q-Rung Interval-Valued Orthopair Fuzzy Information and Its Application to Supplier Selection of Medical Consumption Products. *International Journal of Environmental Research and Public Health*, 17(2), 525. doi:10.3390/ijerph17020525 [[Crossref](#)], [[Web of Science ®](#)], [[Google Scholar](#)]
10. Gou, X. J., Xu, Z. S., & Liao, H. C. (2017). Multiple criteria decision making based on Bonferroni means with hesitant fuzzy linguistic information. *Soft Computing*, 21(21), 6515–6529. doi:10.1007/s00500-016-2211-1 [[Crossref](#)], [[Web of Science ®](#)], [[Google Scholar](#)]
11. He, Y., Lei, F., Wei, G. W., Wang, R., Wu, J., & Wei, C. (2019). EDAS method for multiple attribute group decision making with probabilistic uncertain linguistic information and its application to green supplier selection. *International Journal of Computational Intelligence Systems*, 12, 1361–1370. [[Crossref](#)], [[Web of Science ®](#)], [[Google Scholar](#)]
12. Herrera, F., & Martinez, L. (2000). A 2-tuple fuzzy linguistic representation model for computing with words. *IEEE Transactions on Fuzzy Systems*, 8, 746–752. doi:10.1109/91.890332 [[Crossref](#)], [[Web of Science ®](#)], [[Google Scholar](#)]
13. He, T. T., Wei, G. W., Lu, J. P., Wei, C., & Lin, R. (2019). Pythagorean 2-Tuple Linguistic Taxonomy Method for Supplier Selection in Medical Instrument Industries. *International Journal of Environmental Research and Public Health*, 16, 4875. doi:10.3390/ijerph16234875 [[Crossref](#)], [[Web of Science ®](#)], [[Google Scholar](#)]

143. doi:10.1007/s00500-018-3501-6 [[Crossref](#)], [[Web of Science ®](#)], [[Google Scholar](#)]
15. Kung, C. Y., & Wen, K. L. (2007). Applying Grey Relational Analysis and Grey Decision-Making to evaluate the relationship between company attributes and its financial performance - A case study of venture capital enterprises in Taiwan. *Decision Support Systems*, 43(3), 842–852. doi:10.1016/j.dss.2006.12.012 [[Crossref](#)], [[Web of Science ®](#)], [[Google Scholar](#)]
16. Kuo, Y., Yang, T., & Huang, G. W. (2008). The use of grey relational analysis in solving multiple attribute decision-making problems. *Computers & Industrial Engineering*, 55, 80–93. doi:10.1016/j.cie.2007.12.002 [[Crossref](#)], [[Web of Science ®](#)], [[Google Scholar](#)]
17. Lei, F., Wei, G. W., Lu, J. P., Wei, C., & Wu, J. (2019). GRA method for probabilistic linguistic multiple attribute group decision making with incomplete weight information and its application to waste incineration plants location problem. *International Journal of Computational Intelligence Systems*, 12, 1547–1556. [[Crossref](#)], [[Web of Science ®](#)], [[Google Scholar](#)]
18. Liao, H., Jiang, L., Lev, B., & Fujita, H. (2019). Novel operations of PLTSs based on the disparity degrees of linguistic terms and their use in designing the probabilistic linguistic ELECTRE III method. *Applied Soft Computing*, 80, 450–464. doi:10.1016/j.asoc.2019.04.018 [[Crossref](#)], [[Web of Science ®](#)], [[Google Scholar](#)]
19. Li, Z. X., & Lu, M. (2019). Some novel similarity and distance and measures of Pythagorean fuzzy sets and their applications. *Journal of Intelligent & Fuzzy Systems*, 37, 1781–1799. doi:10.3233/JIFS-179241 [[Crossref](#)], [[Web of Science ®](#)], [[Google Scholar](#)]
20. Lin, M. W., Xu, Z. S., Zhai, Y. L., & Yao, Z. Q. (2018). Multi-attribute group decision-making under probabilistic uncertain linguistic environment. *Journal of the Operational Research Society*, 69(2), 157–170. doi:10.1057/s41274-017-0182-y [[Taylor & Francis Online](#)], [[Web of Science ®](#)], [[Google Scholar](#)]

- Technological and Economic Development of Economy, 26(1), 86–102.
doi:10.3846/tede.2019.11333 [[Crossref](#)], [[Web of Science ®](#)], [[Google Scholar](#)]
22. Lu, J. P., & Wei, C. (2019). TODIM method for performance appraisal on social-integration-based rural reconstruction with interval-valued intuitionistic fuzzy information. *Journal of Intelligent & Fuzzy Systems*, 37, 1731–1740.
doi:10.3233/JIFS-179236 [[Crossref](#)], [[Web of Science ®](#)], [[Google Scholar](#)]
23. Lu, J. P., Wei, C., Wu, J., & Wei, G. W. (2019). TOPSIS method for probabilistic linguistic MAGDM with entropy weight and its application to supplier selection of new agricultural machinery products. *Entropy*, 21(10), 953.
doi:10.3390/e21100953 [[Crossref](#)], [[Web of Science ®](#)], [[Google Scholar](#)]
24. Malek, A., Ebrahimnejad, S., & Tavakkoli-Moghaddam, R. (2017). An improved hybrid grey relational analysis approach for green resilient supply chain network assessment. *Sustainability*, 9(8), 1433. doi:10.3390/su9081433
[[Crossref](#)], [[Web of Science ®](#)], [[Google Scholar](#)]
25. Pamucar, D., & Cirovic, G. (2015). The selection of transport and handling resources in logistics centers using Multi-Attributive Border Approximation area Comparison (MABAC). *Expert Systems with Applications*, 42, 3016–3028.
[[Crossref](#)], [[Web of Science ®](#)], [[Google Scholar](#)]
26. Pang, Q., Wang, H., & Xu, Z. S. (2016). Probabilistic linguistic term sets in multi-attribute group decision making. *Information Sciences*, 369, 128–143.
doi:10.1016/j.ins.2016.06.021 [[Crossref](#)], [[Web of Science ®](#)], [[Google Scholar](#)]
27. Rodriguez, R. M., Martinez, L., & Herrera, F. (2012). Hesitant fuzzy linguistic term sets for decision making. *IEEE Transactions on Fuzzy Systems*, 20(1), 109–119.
doi:10.1109/TFUZZ.2011.2170076 [[Crossref](#)], [[Web of Science ®](#)], [[Google Scholar](#)]
28. Stanujkic, D., Karabasevic, D., Zavadskas, E. K., Smarandache, F., & Brauers, W. K. M. (2019). A bipolar fuzzy extension of the MULTIMOORA method. *Informatica*,

29. Stevic, Z., Vasiljevic, M., Zavadskas, E. K., Sremac, S., & Turskis, Z. (2018). Selection of carpenter manufacturer using fuzzy EDAS Method. *Engineering Economics*, 29, 281–290. doi:10.5755/j01.ee.29.3.16818 [[Crossref](#)], [[Web of Science ®](#)], [[Google Scholar](#)]
30. Sun, G. D., Guan, X., Yi, X., & Zhou, Z. (2018). Grey relational analysis between hesitant fuzzy sets with applications to pattern recognition. *Expert Systems with Applications*, 92, 521–532. doi:10.1016/j.eswa.2017.09.048 [[Crossref](#)], [[Web of Science ®](#)], [[Google Scholar](#)]
31. Tan, Y. S., Chen, H., & Wu, S. (2019). Evaluation and implementation of environmentally conscious product design by using AHP and grey relational analysis approaches. *Ekoloji*, 28, 857–864. [[Google Scholar](#)]
32. Tian, G., Zhang, H., Feng, Y., Jia, H., Zhang, C., Jiang, Z., ... Li, P. (2017). Operation Patterns Analysis of Automotive Components Remanufacturing Industry Development in China. *Journal of Cleaner Production*, 64, 1363–1375. doi:10.1016/j.jclepro.2017.07.028 [[Crossref](#)], [[Web of Science ®](#)], [[Google Scholar](#)]
33. Tian, G. D., Zhang, H. H., Feng, Y. X., Wang, D. Q., Peng, Y., & Jia, H. F. (2018). Green decoration materials selection under interior environment characteristics: A grey-correlation based hybrid MCDM method. *Renewable & Sustainable Energy Reviews*, 81, 682–692. [[Crossref](#)], [[Web of Science ®](#)], [[Google Scholar](#)]
34. Tian, G., Hao, N., Zhou, M., Pedrycz, Witold, Chaoyong, Z., Ma, F., & Li, Z. (2019). Fuzzy Grey Choquet Integral for Evaluation of Multicriteria Decision Making Problems With Interactive and Qualitative Indices. *IEEE Transactions on Systems, Man, and Cybernetics: Systems*, 10.1109/TSMC.2019.2906635 [[Google Scholar](#)]
35. Torra, V. (2010). Hesitant Fuzzy Sets. *International Journal of Intelligent Systems*, 25, 529–539. doi:10.1002/int.20418 [[Crossref](#)], [[Web of Science ®](#)], [[Google Scholar](#)]

- Intelligent & Fuzzy Systems, 37, 1741–1752. doi:10.3233/JIFS-179237
[\[Crossref\]](#), [\[Web of Science ®\]](#), [\[Google Scholar\]](#)
37. Wang, J., Gao, H., & Lu, M. (2019). Approaches to strategic supplier selection under interval neutrosophic environment. *Journal of Intelligent & Fuzzy Systems*, 37, 1707–1730. doi:10.3233/JIFS-179235 [\[Crossref\]](#), [\[Web of Science ®\]](#), [\[Google Scholar\]](#)
38. Wang, J., Gao, H., & Wei, G. W. (2019). The generalized Dice similarity measures for Pythagorean fuzzy multiple attribute group decision making. *International Journal of Intelligent Systems*, 34(6), 1158–1183. doi:10.1002/int.22090
[\[Crossref\]](#), [\[Web of Science ®\]](#), [\[Google Scholar\]](#)
39. Wang, J., Lu, J. P., Wei, G. W., Lin, R., & Wei, C. (2019). Models for MADM with Single-Valued Neutrosophic 2-Tuple Linguistic Muirhead Mean Operators. *Mathematics*, 7(5), 442. doi:10.3390/math7050442 [\[Crossref\]](#), [\[Web of Science ®\]](#), [\[Google Scholar\]](#)
40. Wang, J., Wei, G. W., Lu, J. P., Alsaadi, F. E., Hayat, T., Wei, C., & Zhang, Y. (2019). Some q-rung orthopair fuzzy Hamy mean operators in multiple attribute decision-making and their application to enterprise resource planning systems selection. *International Journal of Intelligent Systems*, 34(10), 2429–2458. doi:10.1002/int.22155 [\[Crossref\]](#), [\[Web of Science ®\]](#), [\[Google Scholar\]](#)
41. Wei, G. W., Wang, R., Wang, J., Wei, C., & Zhang, Y. (2019). Methods for Evaluating the Technological Innovation Capability for the High-Tech Enterprises With Generalized Interval Neutrosophic Number Bonferroni Mean Operators. *IEEE Access*, 7, 86473–86492. doi:10.1109/ACCESS.2019.2925702 [\[Crossref\]](#), [\[Web of Science ®\]](#), [\[Google Scholar\]](#)
42. Wei, G. W., Wei, C., Wu, J., & Wang, H. J. (2019). Supplier selection of medical consumption products with a probabilistic linguistic MABAC method. *International Journal of Environmental Research and Public Health*, 16(24), 5082. doi:10.3390/ijerph16245082 [\[Crossref\]](#), [\[Web of Science ®\]](#), [\[Google Scholar\]](#)

Ekonomiska Istrazivanja, 32, 1498–1520.

[Taylor & Francis Online], [Web of Science ®], [Google Scholar]

44. Wei, G. W., Wang, J., Wei, C., Wei, Y., & Zhang, Y. (2019). Dual Hesitant Pythagorean Fuzzy Hamy Mean Operators in Multiple Attribute Decision Making. *IEEE Access.*, 7, 86697–86716. doi:10.1109/ACCESS.2019.2924974 [Crossref], [Web of Science ®], [Google Scholar]
45. Wei, G. W., Wu, J., Wei, C., Wang, J., & Lu, J. P. (2019). Models for MADM with 2-tuple linguistic neutrosophic Dombi Bonferroni mean operators. *IEEE Access*, 7, 108878–108905. doi:10.1109/ACCESS.2019.2930324 [Crossref], [Web of Science ®], [Google Scholar]
46. Wu, L. P., Gao, H., & Wei, C. (2019). VIKOR method for financing risk assessment of rural tourism projects under interval-valued intuitionistic fuzzy environment. *Journal of Intelligent & Fuzzy Systems*, 37, 2001–2008. doi:10.3233/JIFS-179262 [Crossref], [Web of Science ®], [Google Scholar]
47. Wu, L. P., Wang, J., & Gao, H. (2019). Models for competitiveness evaluation of tourist destination with some interval-valued intuitionistic fuzzy Hamy mean operators. *Journal of Intelligent & Fuzzy Systems*, 36, 5693–5709. doi:10.3233/JIFS-181545 [Crossref], [Web of Science ®], [Google Scholar]
48. Wu, L. P., Wei, G. W., Wu, J., & Wei, C. (2020). Some Interval-Valued Intuitionistic Fuzzy Dombi Heronian Mean Operators and their Application for Evaluating the Ecological Value of Forest Ecological Tourism Demonstration Areas. *International Journal of Environmental Research and Public Health*, 17(3), 829. doi:10.3390/ijerph17030829 [Crossref], [Web of Science ®], [Google Scholar]
49. Xie, W. Y., Ren, Z. L., Xu, Z. S., & Wang, H. (2018). The consensus of probabilistic uncertain linguistic preference relations and the application on the virtual reality industry. *Knowledge-Based Systems*, 162, 14–28. [Crossref], [Web of Science ®], [Google Scholar]

Information Sciences, 168(1-4), 171–184. doi:10.1016/j.ins.2004.02.003

[\[Crossref\]](#), [\[Web of Science ®\]](#), [\[Google Scholar\]](#)

51. Xu, Z. S. (2005). Deviation measures of linguistic preference relations in group decision making. *Omega-International Journal of Management Science*, 33(3), 249–254. doi:10.1016/j.omega.2004.04.008 [\[Crossref\]](#), [\[Web of Science ®\]](#), [\[Google Scholar\]](#)
52. Zadeh, L. A. (1975). The concept of a linguistic variable and its application to approximate reasoning. *Information Sciences*, 8(4), 301–357. doi:10.1016/0020-0255(75)90046-8 [\[Crossref\]](#), [\[Web of Science ®\]](#), [\[Google Scholar\]](#)
53. Zavadskas, E. K., Antucheviciene, J., Sapraskas, J., & Turskis, Z. (2013). MCDM methods WASPAS and MULTIMOORA: Verification of robustness of methods when assessing alternative solutions. *Economic Computation and Economic Cybernetics Studies and Research*, 47, 5–20. [\[Web of Science ®\]](#), [\[Google Scholar\]](#)
54. Zhang, K., Kong, W. R., Liu, P. P., Shi, J., Lei, Y., & Zou, J. (2018). Assessment and sequencing of air target threat based on intuitionistic fuzzy entropy and dynamic VIKOR. *Journal of Systems Engineering and Electronics*, 29(2), 305–310. doi:10.21629/JSEE.2018.02.11 [\[Crossref\]](#), [\[Web of Science ®\]](#), [\[Google Scholar\]](#)
55. Zhang, S. Q., Wei, G. W., Gao, H., Wei, C., & Wei, Y. (2019). EDAS method for multiple criteria group decision making with picture fuzzy information and its application to green suppliers selections. *Technological and Economic Development of Economy*, 26, 1123–1138. doi:10.3846/tede.2019.10714 [\[Crossref\]](#), [\[Web of Science ®\]](#), [\[Google Scholar\]](#)

[Download PDF](#)



Related research 

methods using GIS >

Dogus Guler et al.

Annals of GIS

Published online: 9 Mar 2020



The risk assessment of construction project investment based on prospect theory with linguistic preference orderings >

Xunjie Gou et al.

Economic Research-Ekonomska Istraživanja

Published online: 17 Jan 2021



Wasserstein distance-based probabilistic linguistic TODIM method with application to the evaluation of sustainable rural tourism potential >

Shitao Zhang et al.

Economic Research-Ekonomska Istraživanja

Published online: 18 Mar 2021



[View more](#)

Information for

[Authors](#)

[R&D professionals](#)

[Editors](#)

[Librarians](#)

[Societies](#)

Opportunities

[Reprints and e-prints](#)

[Advertising solutions](#)

[Accelerated publication](#)

[Corporate access solutions](#)

Open access

[Overview](#)

[Open journals](#)

[Open Select](#)

[Dove Medical Press](#)

[F1000Research](#)

Help and information

[Help and contact](#)

[Newsroom](#)

[All journals](#)

[Books](#)

Keep up to date

Register to receive personalised research and resources by email

 [Sign me up](#)



[Copyright © 2022 Informa UK Limited](#) [Privacy policy](#) [Cookies](#) [Terms & conditions](#)

[Accessibility](#)

 **Taylor & Francis Group**
an **informa** business

Registered in England & Wales No. 3099067
5 Howick Place | London | SW1P 1WG