



Open access

2,125 Views | 14 CrossRef citations to date | 9 Altmetric

Listen

Original Articles

Reconfigurable DC Links for Restructuring Existing Medium Voltage AC Distribution Grids

Aditya Shekhar , Laura Ramírez-Elizondo, Xianyong Feng ,
Epaminondas Kontos & Pavol Bauer

Pages 1739-1746 | Received 18 Nov 2016, Accepted 14 Jun 2017, Published online: 16 Jan 2018

Cite this article <https://doi.org/10.1080/15325008.2017.1346005>

Check for updates

Full Article

Figures & data

References

Citations

Metrics

Licensing

Reprints

We Care About Your Privacy

We and our 909 partners store and access personal data, like browsing data or unique identifiers, on your device. Selecting I Accept enables tracking technologies to support the purposes shown under we and our partners process data to provide. Selecting Reject All or withdrawing your consent will disable them. If trackers are disabled, some content and ads you see may not be as relevant to you. You can resurface this menu to change your choices or withdraw consent at any time by clicking the Show Purposes link on the bottom of the webpage. Your choices will have effect within our Website. For more details, refer to our Privacy Policy. [Here](#)

We and our partners process data to provide:

Use precise geolocation data. Actively scan device

I Accept

Reject All

Show Purposes

paper revolve around, is to present a viable way of gradual transition from AC to hybrid AC-DC to finally a universal DC system.


Keywords::

- AC
- DC
- distribution
- grids
- reconfiguration
- flexibility
- restructure

1. Introduction

Increasing integration of dispersed renewable energy sources in existing electricity supply systems has enabled bidirectional power flows in the AC distribution networks. New energy consumers like electric vehicles, all electric houses, and heat pumps have changed the localized energy consumption patterns and increased the expected demand from grid infrastructure several folds [1,2]. Infrastructural complexity and investment costs are required for maintaining sufficient and optimized power flows to cope with localized demand deficits and quality of supply at acceptable voltage deviations. The distribution network operators should have adequate flexibility and control on the grid operation. Reconfigurable DC links incorporated in the existing AC distribution grids can provide solutions to the challenges highlighted in the subsequent section.

As [3] like lower loss, bidirectional power flow, and storage, while off-grid, such as converter-link, converter-grid, and are listed and highlighted.



TABLER
DC-based

Download

Related research

The subsequent section elaborates on these challenges and opportunities. Then, the new concepts developed in this paper are presented and their potential is identified by reviewing the existing conventional practices. Finally, the limitations of the DC link technology and the means of mitigating them are discussed.

2. Challenges and Opportunities

2.1. Increase in Power Demand

A shift toward electric energy from traditional fossil fuel use in vehicles and heat pumps may trigger the need to enhance the capacity of existing distribution grids [4].

- Electric vehicles (EVs) have high charging power demand. User behaviour of charging the EVs at certain scheduled time of the day could create local overload on the grid even though the installed capacity is enough for average loading conditions [25].
- Interest in adopting all-electric houses has increased the reliance on electrical energy [26]. Some DNOs expect a significant hike in demand on their grid infrastructure if electrical heat pumps are used instead of conventionally used gas pipes.



require an intermediate AC-DC-AC conversion stage. A DC interconnection can lead to the reduction in a conversion stage, thereby improving the efficiency. The creation of flexible DC nano-grids controlled independently in a distributed way and interconnected via a DC grid in an open energy system may lead to de-congestion and solve problems of intermittent nature of generation locally [7,10].

3.1. Meshing and Redundancies

The ability to revert to AC when the DC link operation fails during contingency is an important requirement, particularly at critical locations of bulk power transfer. Therefore, the architecture proposed is hardware-reconfigurable with the possibility of operating in both AC and DC.

An advantage of interconnecting different grid locations, thereby creating active closed loop grid architectures, is anticipated to fundamentally change how the future power grids will be designed and operated. The concepts such as network and fault reconfiguration of existing AC networks using optimally placed DC links are a pioneering focus of this paper.

3.2. Operational Flexibility

Big data applications in power utilities appear to be the next logical step toward smarter grids. The volume of data generated by smart meters and sensors can reach its full potential only when the data is processed and analyzed. As the data volume increases, the need for a robust data management system becomes critical. The control system must be able to handle the large volume of data and make necessary decisions. The reconfiguration of the grid is a necessary layer. The evolution of the grid is a continuous process.



4. Novel

This paper proposes a novel architecture for a distributed energy system. The system is designed to be flexible and scalable, allowing for the integration of existing AC and DC networks. The architecture is based on a universal principle that can be applied to a wide range of power systems.

redundancy at critical grid locations.

- Control reconfigurability for greater flexibility and grid-supporting ancillary services.
- Network reconfigurability for loss minimization and feeder load redistribution using DC links.
- Fault reconfigurability for achieving higher availability.

This section explores the potential of these ideas further and supports their viability by highlighting the current and anticipated limitations of conventional AC utility grid architecture, control, and practices.

4.1. Hardware Reconfigurability

[Figure 3](#) depicts one of the hardware system reconfigurations that can work as a bipolar DC link as well as revert to a three-phase AC operation during converter faults by a modular repair scheme. In this scheme, the three core cables operate as a bipolar DC link under normal operational conditions. Two of the cables can be fully loaded, while one is either redundant or acts as a return path as shown in [Figure 3\(a\)](#). During converter faults, which are the least reliable part of the system, the circuit breakers on the AC side open and the faulted components can be modularly removed as shown in [Figure 3\(b\)](#). The system can revert back to a three-phase three-line AC operation as shown in [Figure 3\(c\)](#). The system can also operate as a bipolar DC link at both sides.

FIGURE 3 | Hardware reconfigurability of the system. (a) Normal operation. (b) Faulted components removed. (c) Revert back to three-phase three-line AC operation. (d) Bipolar DC link operation. (e) Bipolar DC link operation with ground cables.




grids which are then operated in a radial mode and restructured using switching operations through efficient optimization techniques [14]. While such techniques of branch exchanges for the network reconfiguration have been explored extensively in the literature, the radial constraint is respected in all such studies [11–16].

Interestingly, it was noted as an afterthought in [16] that if a network configuration with a limited number of loops could be allowed, substantial reduction of resistive line losses over those of the optimum radial configuration may also be achieved.

Considering that at the distribution level, a looped operation was unfavorable for AC, this was never explored further.

Considering that the point-to-point DC links can asynchronously interconnect two AC grid locations, it can be easily appreciated that the benefits of “radial” AC operation and network reconfiguration for loss minimization, load balancing, service restoration, and reactive power support using a flexible DC link backbone can be combined [24]. The An optimal placement of dc links in existing ac distribution networks can be beneficial, as illustrated in Figure 4.

FIGURE 4. Network restructuring using reconfigurable DC links.



Trade-offs in terms of cost of front and back convertors for DC links and their operating losses are added constraints, while new benefits such as rapid response, better control, efficient cable operation, enhancement in power transfer capability, and flexibility with ancillary services like harmonic elimination, power redirection, and voltage support should be incorporated in future problem formulations in this field.

The most interesting potential of this concept is the scalability of a multi-terminal DC skeleton within the existing AC grid, integrating distributed generation resources and energy-intensive consumers to achieve a “Grid within a grid,” therefore, paving way for the vision of realistically transitioning toward a universal DC distribution in a systematic way, as illustrated in [Figure 4](#).

4.3. Fault Reconfigurability

The hybrid AC/DC medium-voltage system has great advantages over conventional AC distribution systems. In the conventional AC system, the tie switches are usually used to achieve service restoration once the fault occurs. This existing fault mitigation strategy has some disadvantages. First, after the fault is isolated, the downstream loads would be interrupted before they are reenergized by another feeder. Second, the new network topology caused by the closing of tie switch will cause high system losses and poor voltage profiles along the feeder since the closing of tie switch makes the main feeder much longer. The healthy radial AC system with a single point-to-point reconfig

FIGURE 1



Display full

In case (b), when fault F1 occurs between R12 and R13, that section is isolated and the nodes from R13 and end point are fed by closing the NO tie-line. The DC link converters generally have a fault ride through capability and can remain in operation. In this case, there is not much difference as compared to the system without the DC link, apart from the fact that the performance can be better due to inherent tolerance to over-currents and the capability to support the node voltage.

In case (c), when fault F2 occurs near the main bus, the DC link can provide supply to a downstream node and it is not necessary to switch in the tie-line. Apart from reducing the number of switching operations, this scenario also results in a better voltage profile and lower losses. It also does not result in a change in the current direction, which is an issue with an over-current relay coordination discussed in [15].

Similarly, in case (d), fault F3 can be isolated without interrupting the supply to other loads and avoiding the need to operate the tie-line. Therefore, it can be concluded that any fault between the main bus and the DC link end will reduce the tie-line operation and the losses, while improving the overall voltage profile. For faults between the DC link end and the tie-line, the fault ride through can guarantee a similar better performance than the original system.

It is also important to consider the constraints' relay coordination (R11-R14 and R21-R24) which is applied to the network reconfigurability. In the conventional radial system reconfig, some branches are opened and some are closed. The placement of the DC link is also important.

4.4. Co

Exc
Gener
al
bl
cl



Display full

DC link

other as shown in [Figure 6](#). In case there is excess generation due to distributed sources in phase a1 in one part of the grid and local power deficit due to high demand in phase c2 in another part, the power can be redirected easily, efficiently, and rapidly by reconfiguring the converters without synchronization issues. This redirection may be beneficial in low-voltage microgrids with local pockets of power surplus and deficits. An adequate control algorithm for the DC links can offer flexibility in the operation of the distribution grid.

- If a bipolar configuration is employed, the system can be reconfigured to operate in a monopolar mode for limited time [\[1\]](#) with 50% capacity during single-line faults.
- Flexible operation of link converters as STATCOM for reactive power injection and harmonic elimination when the link is operating under AC conditions.

5. Limitations in Employing Reconfigurable DC Link Technology

Given the less mature market for DC technologies, particularly in terms of DC breakers [\[17\]](#) and minimal penetration of DC transmission in MV/LV distribution grids, point-to-point connections as a flexible backbone to the AC network are preferable as the starting point. To have more meshed interconnection and renewable energy integration toward the future, the following limitations should be considered:

- High inductance of the DC link may lead to high voltage overshoots during fault clearing. It should be balanced with the DC link capacitance, and the flexible operation of the link should be considered.
- Protection of the DC link is a challenge. Short-circuit protection is a trade-off between the protection speed and the DC link capacitance.
- Power quality issues may arise due to the presence of harmonics and noise. Proper filtering and control strategies should be used for the link converters.
- Converter losses and thermal management are critical for the long-term operation of the DC link.



6. Conclusion

Installing reconfigurable DC links in existing AC distribution networks can offer modularity and redundancy, flexibility of operation, and optimized power flow with loss minimization, as well as better availability and performance during faults. The novel ideas presented in this paper open an entirely new research direction in designing future hybrid power systems with a more involved AC and DC integration.

Hardware reconfigurability to achieve a modular AC-DC link operation not only allows grid operators to test the operational benefits of DC power transfer, but also gives them the option to revert to AC operation during contingencies like link converter fault, which are the least reliable part of the proposed system. Common use of circuit breakers and cables during AC and DC operations offers savings in infrastructure costs incurred.

Network reconfigurability with DC link breaks a limiting radial constraint that the AC distribution system imposed in the load balancing and loss minimization problems. The proposed concept is scalable to multi-terminal DC systems. An efficient interconnection of DC-distributed generation sources like PV and energy-intensive consumers like EVs makes it possible to integrate a DC “nano-grid within the grid.”

In fault recovery, the proposed system can be configured to isolate the faulted area and restore service to the healthy part of the network. This would be better than the traditional AC system where the faulted area is isolated and the entire network is reconfigured. The cost of the proposed system is expected to be lower than the cost of an all-AC system. The vision of a future power system with an all-AC distribution network is still a challenge.



Acknowledgments

This work was supported by the Dutch Ministry of Economic Affairs and Climate Policy (VWS) under the Future Energy Consumer Centres (F4E3) programme. The authors would like to thank the participants of the Power Line Integration (PLI) project for their contributions. The authors would like to thank the Dutch Ministry of Economic Affairs and Climate Policy (VWS) for the support of the PLI project. The authors would like to thank the utility companies for their support in the PLI project.

Additional information

Funding

TKI Switch2SmartGrids(FLINK)

Notes on contributors

Aditya Shekhar

Aditya Shekhar is currently pursuing his Ph.D. in Delft University of Technology. He was a guest researcher in The University of Texas at Austin in the fall of 2016. He completed his M.Sc. in electrical sustainable energy in 2015 with cum laude from the Delft University of Technology. He was awarded the IDEA League Scholarship to work on his M.Sc. thesis in ETH, Zurich, in the High Voltage Laboratory. He was also given an honors degree for his internship work in TNO, the Netherlands, in the field of solar roads and wireless energy transfer. He finished his bachelor's degree in electrical with distinction in 2010 from National Institute of Technology, Surat, India, and gained experience as a field engineer in Uniphos Ltd. Later, he worked as a researcher in IIT, Bombay, India, for exploring energy conservation, benchmarks, and renewable energy transition studies for railways. His research

Laura I

Laura P

Conver

Elec

Pia

her M.S

Techno

Delft U

various



Xianyong Feng

Xianyong Feng received his Ph.D. degree in the Department of Electrical and Computer Engineering at Texas A&M University, College Station, TX, USA, in May 2012. He is currently with Center for Electromechanics, The University of Texas at Austin. Prior to that, Dr. Feng worked with ABB, Raleigh, NC, USA, and ExxonMobil, Houston, TX, USA. His research interests are in the areas of microgrids, shipboard power systems, and DC power system protection.

Epaminondas Kontos

Epameinondas Kontos was born in Greece in 1988. He received the M.Sc. (Hons.) degree in sustainable energy technology from the Delft University of Technology (TU Delft), Delft, the Netherlands, in 2013. Since 2013, he has been a Ph.D. Researcher with the TKI Synergies at Sea Project at the DC&S Group of TU Delft. His research interests include various topics of electric power engineering.

Pavol Bauer

Pavol Bauer is an Associate Professor in the Department of Sustainable Energy Systems at TU Delft. He is also a senior research advisor at the DC&S Group. He has published over 50 journal articles and is co-author of several books and tutorial papers. He is also a senior advisor for industrial projects and has developed several applications for distributed energy storage, charging and discharging of batteries, and project management (PEMCV). His research interests are in the areas of sustainable energy systems, microgrids, and DC power systems.



Related Research Data

System design for a solar powered electric vehicle charging station for workplaces

Source: Applied Energy

Optimal capacitor placement on radial distribution systems

Source: IEEE Transactions on Power Delivery

Providing dc fault ride-through capability to H-bridge MMC-based HVDC networks

Source: Unknown Repository

The Alternate Arm Converter: A New Hybrid Multilevel Converter With DC-Fault Blocking Capability

Source: IEEE Transactions on Power Delivery

Trends in Microgrid Control

Source: IEEE Transactions on Smart Grid

Hybrid Multilevel Converter With Cascaded H-bridge Cells for HVDC Applications: Operating Principle and Scalability

Source:

Technique for the design of a multilevel converter for HVDC applications

Source:

Source:

Impact of the dc fault on the power quality of the ac system

Balance

Source:

Optimal placement of the dc fault on the power quality of the ac system

Source:

Source:

Optim

Manag

Source:

Dete

own



Conceptual Study for Open Energy Systems: Distributed Energy Network Using Interconnected DC Nanogrids

Source: IEEE Transactions on Smart Grid

AC-microgrids versus DC-microgrids with distributed energy resources: A review

Source: Renewable and Sustainable Energy Reviews

AC and DC technology in microgrids: A review

Source: Renewable and Sustainable Energy Reviews

Impact of HVDC transmission system topology on multiterminal DC network faults

Source: Unknown Repository

A Review on HVDC Circuit Breakers

Source: Unknown Repository

Grid capacity and efficiency enhancement by operating medium voltage AC cables as DC links with modular multilevel converters

Source: International Journal of Electrical Power & Energy Systems

Modelling the Weekly Electricity Demand Caused by Electric Cars

Source: Procedia Computer Science

Power electronics as efficient interface in dispersed power generation systems

Source: IEEE Transactions on Power Electronics

Refurbishment of a power distribution network for smart grid conditions

Source: Unknown Repository

Network reconfiguration for load balancing in a smart grid

balancing

Source: Unknown Repository

Distributed energy storage in a smart grid

Conservation

Source: Unknown Repository

Feasibility

Source: Unknown Repository

Recovery

Reduction

Source: Unknown Repository

The impact

Source: Unknown Repository



Source: Unknown Repository

HVDC Conversion of HVAC Lines to Provide Substantial Power Upgrading

Source: IEEE Power Engineering Review

Linking provided by [ScholeXplorer](#)

References

1. Chandra Mouli, G. R., Bauer, P., and Zeman, M., "System design for a solar powered electric vehicle charging station for workplaces," Appl. Energy., Vol 168, 15 April 2016.

[Web of Science ®](#) | [Google Scholar](#)

2. Gustafsson, M., Gustafsson, M. S., Myhren, J. A., Bales, C., and Holmberg, S., "Techno-economic analysis of energy renovation measures for a district heated multi-family house," Appl. Energy, Vol. 177, 2016.

[PubMed](#) | [Web of Science ®](#) | [Google Scholar](#)

3. Justo, J. J., Mwasilu, F., Lee, J., and Jung, J., "AC-microgrids versus DC-microgrids with distrib

4. Shekh... P.,
"Refur... ditions,"
Power... International,
Varna

Go

5. Blaabj... interface in
disper... 9, No. 5, pp.
1184-



6. Planas, E., Andreu, J., Gárate, J. I., de Alegría, I. M., and Ibarra, E., "AC and DC technology in microgrids: A review," *Renew. Sust Energy Rev.*, Vol. 43, March 2015.

[Web of Science ®](#) | [Google Scholar](#)

7. Olivares, D. E., Mehrizi-Sani, A., Etemadi, A. H., Canizares, C. A., Iravani, R., Kazerani, M., Hajimiragha, A. H., Gomis-Bellmunt, O., Saeedifard, M., Palma-Behnke, R., Jimenez-Estevez, G. A., and Hatziargyriou, N. D., "Trends in microgrid control," *Smart Grid IEEE Trans.*, Vol. 5, No. 4, pp. 1905–1919, July 2014.

[Web of Science ®](#) | [Google Scholar](#)

8. Werth, A., Kitamura, N., and Tanaka, K., "Conceptual Study for open energy systems: Distributed energy network using interconnected DC nanogrids," *Smart Grid IEEE Trans.*, Vol. 6, No. 4, pp. 1621–1630, July 2015.

[Web of Science ®](#) | [Google Scholar](#)

9. Lai, C. S., and McCulloch, M. D., "Big data analytics for smart grid," (2015) Retrieved from <http://smartgrid.ieee.org/newsletters/october-2015/big-data-analytics-for-smart-grid>. Accessed 01.02.17.

[Google Scholar](#)

10. Hashem, A., and Ahmed, E., "A review of smart grid technologies," *Renew. Sust Energy Rev.*, Vol. 36, No. 5, pp. 109–120, May 2014.

11. Baran, M. H., and Veerachandran, P., "A review of smart grid technologies for loss reduction," *Renew. Sust Energy Rev.*, Vol. 14, No. 1, pp. 1401–1407, April 2010.

12. Baran, M. H., and Veerachandran, P., "A review of smart grid technologies for loss reduction," *Renew. Sust Energy Rev.*, Vol. 14, No. 1, pp. 1401–1407, April 2010.



3. Zidan, A., and El-Saadany, E. F., "Impacts of feeder reconfiguration on renewable resources allocation in balanced and unbalanced distribution systems," 2012 IEEE Power and Energy Society General Meeting, San Diego, CA, 2012, pp. 1-8.

[Google Scholar](#)

4. Jiang, D., and Baldick, R., "Optimal electric distribution system switch reconfiguration and capacitor control," IEEE Trans. Power Syst., Vol. 11, No. 2, pp. 890-897, May 1996.

5. Bhattacharya, S. K., and Goswami, S. K., "Distribution network reconfiguration considering protection coordination constraints," J. Electr. Power Comp. Syst., Taylor and Francis, Vol. 44, pp. 974-989, May 2016.

[Google Scholar](#)

6. Shirmohammadi, D., and Hong, H. W., "Reconfiguration of electric distribution networks for resistive line losses reduction," IEEE Trans. Power Deliv., Vol. 4, No. 2, pp. 14

7. Jovcic, "Feasibility of DC transmission (Europe), 2011 2 nd I... mber 2011.



8. Kontos, "Transmission system... ans., Vol. 30, No

9. Kontos, E., Pinto, R. T., and Bauer, P., "Providing dc fault ride-through capability to H-bridge MMC-based HVDC networks," Power Electronics and ECCE Asia (ICPE-ECCE Asia), 2015 9th International Conference, pp. 1542-1551, 1-5 June 2015.

[Google Scholar](#)

10. Mokherdoran, A., Carvalho, A., Leite, H., and Silva, N., "A review on HVDC circuit breakers," Renewable Power Generation Conference (RPG 2014, 3rd), pp. 1-6, September 2014.

[Google Scholar](#)

11. Bucher, M. K., and Franck, C. M., "Fault current interruption in multiterminal HVDC networks," Power Deliv. IEEE Trans., Vol. 31, No. 1, pp. 87-95, February 2016.

[Web of Science ®](#) [Google Scholar](#)

12. Adam, G. P., Abdelsalam, I. A., Ahmed, K. H., and Williams, B. W., "Hybrid multilevel converter with cascaded H-bridge cells for HVDC applications: Operating principle and scalability," Power Electron. IEEE Trans., Vol. 30, No. 1, pp. 65-77, January 2015.

[Web of Science ®](#) [Google Scholar](#)

13. Merlin, W., and Crookes, B. W., "A new multilevel converter with DCM," IEEE Trans. Power Electron., Vol. 10, No. 3, pp. 310-317, February 1995.

14. Teo, A., and Crookes, B. W., "Optimal operation of a multilevel converter," IEEE Trans. Power Electron., Vol. 10, No. 3, pp. 318-327, February 1995.

15. Mallig, A., and Crookes, B. W., "Optimal operation of a multilevel converter," IEEE Trans. Power Electron., Vol. 10, No. 3, pp. 318-327, February 1995.

Vol. 52, pp. 444-451, 2015, ISSN 1877-0509,

<https://doi.org/10.1016/j.procs.2015.05.012>.

[Google Scholar](#)

26. Jones, R. V., and Lomas, K. J., "Determinants of high electrical energy demand in UK homes: Appliance ownership and use," *Energy and Buildings*., Vol. 117, pp. 71-82, 2016, ISSN 0378-7788, <https://doi.org/10.1016/j.enbuild.2016.02.020>.

[Web of Science ®](#) | [Google Scholar](#)

27. Clerici, A., Paris, L., and Danfors, P., "Hvdc conversion of hvac lines to provide substantial power upgrading," *IEEE Trans on Power Delivery*, Vol. 6, no. 1, pp. 324-333, 1999. doi:10.1109/61.103755.

[Google Scholar](#)

28. Shekhar, A., Kontos, E., Ramírez-Elizondo, L., Mor, A. R., and Bauer, P., "Grid Capacity and Efficiency Enhancement by Operating Medium Voltage AC Cables as DC Links with Modular Multilevel Converters," *J. Electr. Power Energy Syst.*, Elsevier, 2017.

[Web of Science ®](#) | [Google Scholar](#)

Download

Related



Information for

Authors

R&D professionals

Editors

Librarians

Societies

Opportunities

Reprints and e-prints

Advertising solutions

Accelerated publication

Corporate access solutions

Open access

Overview

Open journals

Open Select

Dove Medical Press

F1000Research

Help and information

Help and contact

Newsroom

All journals

Books

Keep up to date



Copyright © 2016 Taylor & Francis Group
Taylor & Francis business

Accessibi

Registered
5 Howick Pl

