

[International Journal of Green Energy](#) >
Volume 13, 2016 - Issue 14

176 | 14 | 0
Views | CrossRef citations to date | Altmetric

Original Articles

Experimental investigation on engine performances, combustion characteristics and emission of exhaust gases of VCR engine fuelled with cottonseed oil methyl ester blended with diesel

M. Santhosh  & K. P. Padmanaban

Pages 1534-1545 | Accepted author version posted online: 10 Dec 2014, Published online: 10 Dec 2014

 [Download citation](#)  <https://doi.org/10.1080/15435075.2014.977438>



Sample our
Economics, Finance,
Business & Industry Journals
>> [Sign in here](#) to start your access
to the latest two volumes for 14 days

 [Full Article](#)  [Figures & data](#)  [References](#)  [Supplemental](#)  [Citations](#)

 [Metrics](#)  [Reprints & Permissions](#)

[Read this article](#)

ABSTRACT

This research work investigates the engine performances, combustion characteristics, and emission of exhaust gases of variable compression ratio engine fuelled with cottonseed oil methyl ester (COME) and diesel at different blends. The analysis showed that heat release rate and cylinder pressure is higher for diesel than COME blends. Higher BTE is obtained at the maximum load condition. The higher BTE and lower SFC are obtained for blend B15 as 42.17% and 0.2 kg/kW-hr at brake mean effective pressure (BMEP) of 4.64 bar. Also it is found that the peak cylinder gas pressure and combustion duration increases when the BMEP increases. At the BMEP of 3.51 bar, higher HRR is observed as 18.12 J/deg. Increase in HRR is obtained as 6.07% for B30 at BMEP of 4.64 bar when compared to diesel. Ignition delay decreased by

13.16% for B100, by the increment of blend proportions when compared to diesel, at BMEP of 4.64 bar. Lower smoke, HC and CO emissions are observed when increasing the blend proportions, whereas the nitric oxide emissions increases due to the better combustion resulted in higher temperatures. At BMEP of 4.64 bar, the CO emissions are reduced to 25.24% for neat biodiesel when compared with the diesel.

KEYWORDS: [Cottonseed oil methyl ester](#) [cylinder pressure](#) [emission](#) [heat release rate](#) [VCR Engine](#)

Acknowledgment

The authors thank the management of PSNA College of Engineering and Technology for providing the necessary experimental setup for this research.

Funding

The authors thank the All India Council for Technical Education (AICTE), Government of India for providing grant (NO.8024/RID/MOD/70/08/09) under Modernization and Removal of Obsolescence (MODROB) scheme for purchase of VCR engine.

Additional information

Funding

The authors thank the All India Council for Technical Education (AICTE), Government of India for providing grant (NO.8024/RID/MOD/70/08/09) under Modernization and Removal of Obsolescence (MODROB) scheme for purchase of VCR engine.



Related research

People also read

Recommended articles

Cited by
14

Information for

[Authors](#)
[R&D professionals](#)
[Editors](#)
[Librarians](#)
[Societies](#)

Opportunities

[Reprints and e-prints](#)
[Advertising solutions](#)
[Accelerated publication](#)
[Corporate access solutions](#)

Keep up to date

Register to receive personalised research and resources by email

 [Sign me up](#)



Open access

[Overview](#)
[Open journals](#)
[Open Select](#)
[Dove Medical Press](#)
[F1000Research](#)

Help and information

[Help and contact](#)
[Newsroom](#)
[All journals](#)
[Books](#)