







Home ▶ All Journals ▶ International Journal of Green Energy ▶ List of Issues ▶ Volume 13, Issue 14 Experimental investigation on engine per

International Journal of Green Energy > Volume 13, 2016 - Issue 14

183 14

Views CrossRef citations to date Altmetric

Original Articles


Experimental investigation on engine performances, combustion characteristics and emission of exhaust gases of VCR engine fuelled with cottonseed oil methyl ester blended with diesel

M. Santhosh 🔀 & K. P. Padmanaban

Pages 1534-1545 | Published online: 10 Dec 2014

66 Cite this article

A https://doi.org/10.1080/15435075.2014.977438



Sample our

We Care About Your Privacy

We and our 861 partners store and access personal data, like browsing data or unique identifiers, on your device. Selecting "I Accept" enables tracking technologies to support the purposes shown under "we and our partners process data to provide," whereas selecting "Reject All" or withdrawing your consent will disable them. If trackers are disabled, some content and ads you see may not be as relevant to you. You can resurface this menu to change your choices or withdraw consent at any time by clicking the ["privacy preferences"] link on the bottom of the webpage [or the floating icon on the bottom-left of the webpage, if applicable]. Your choices will have effect within our Website. For more details, refer to our Privacy Policy. Here

We and our partners process data to provide:

I Accept

Reject All

Show Purpose

acteristics. with vsis showed blends. lower SFC ctive

sure and 51 bar,

% for B30 at

and cottonse that hea Higher B are obta pressure

Full A

Repri

ABSTE

This r

combus higher H BMEP of 4.64 bar when compared to diesel. Ignition delay decreased by 13.16% for B100, by the increment of blend proportions when compared to diesel, at BMEP of 4.64 bar. Lower smoke, HC and CO emissions are observed when increasing the blend proportions, whereas the nitric oxide emissions increases due to the better combustion resulted in higher temperatures. At BMEP of 4.64 bar, the CO emissions are reduced to 25.24% for neat biodiesel when compared with the diesel.

Q KEYWORDS: Cottonseed oil methyl ester cylinder pressure emission heat release rate VCR Engine

Acknowledgment

The authors thank the management of PSNA College of Engineering and Technology for providing the necessary experimental setup for this research.

The authors thank the All India Council for Technical Education (AICTE), Government of India for a result (NO 2024/PID/MOD/70/02/02) and Maderian and Remova

Addit
Fundin
The and Remova

Relat

Homo

inophymum c., kerner on using ortho-phosphone actu as a pretreatment catalyst

um

Source: Informa UK Limited

Physicochemical, Performance, Combustion and Emission Characteristics of Melaleuca

Cajuputi Oil-Refined Palm Oil Hybrid Biofuel Blend

Source: MDPI AG

Linking provided by Schole plorer

Related research 1

People also read

Recommended articles


Cited by 14

A Comparative Analysis of Thermal Performance And Emission Characteristics of Methyl Esters of Karanja And Jatropha Oils Based on A Variable Compression Ratio D... >

H. K. Amarnath et al.

International Journal of Green Energy

Published online: 16 Jan 2014



Information for Open access **Authors** Overview R&D professionals Open journals Editors **Open Select** Librarians **Dove Medical Press** Societies F1000Research Opportunities Help and information Reprints and e-prints Advertising solutions Newsroom Accelerated publication Corporate access solutions Books Keep up to date Register to receive personalised research and resources by email Sign me up X or & Francis Group Copyright Registered 5 Howick Pl