Home ▶ All Journals ▶ International Journal of Green Energy ▶ List of Issues ▶ Volume 13, Issue 14 ▶ Experimental investigation on engine per ....

International Journal of Green Energy > Volume 13, 2016 - Issue 14

182 14 O CrossRef citations to date Altmetric

Original Articles

Experimental investigation on engine performances, combustion characteristics and emission of exhaust gases of VCR engine fuelled with cottonseed oil methyl ester blended with diesel

M. Santhosh 🔀 & K. P. Padmanaban

Pages 1534-1545 | Published online: 10 Dec 2014

 Check for updates

Sample our
Engineering & Technology
Journals

>> Sign in here to start your access to the latest two volumes for 14 days

Full Article

Figures & data

References

**66** Citations

**Metrics** 

% for B30 at

.16% for

Reprints & Permissions

Read this article

# ABSTRACT

higher F

BMEP of 4.04 par

This research work investigates the engine performances, combustion characteristics,

and emi with About Cookies On This Site cottonse sis showed Accept All We and our partners use cookies to enhance your website that hea blends. experience, learn how our site is used, offer personalised Essential Onl lower SFC Higher E features, measure the effectiveness of our services, and tailor content and ads to your interests while you navigate ctive on the web or interact with us across devices. You can Settings choose to accept all of these cookies or only essential sure and cookies. To learn more or manage your preferences, click 51 bar. combus "Settings". For further information about the data we collect from you, please see our Privacy Policy

when compared to dieser, ignition delay

B100, by the increment of blend proportions when compared to diesel, at BMEP of 4.64 bar. Lower smoke, HC and CO emissions are observed when increasing the blend proportions, whereas the nitric oxide emissions increases due to the better combustion resulted in higher temperatures. At BMEP of 4.64 bar, the CO emissions are reduced to 25.24% for neat biodiesel when compared with the diesel.

Q KEYWORDS: Cottonseed oil methyl ester cylinder pressure emission heat release rate VCR Engine

### Acknowledgment


The authors thank the management of PSNA College of Engineering and Technology for providing the necessary experimental setup for this research.

## Funding

The authors thank the All India Council for Technical Education (AICTE), Government of India for providing grant (NO.8024/RID/MOD/70/08/09) under Modernization and Removal of Obsolescence (MODROB) scheme for purchase of VCR engine.

### Additional information

### Funding



from you, please see our Privacy Policy

Information for

**Authors** 

R&D professionals

**Editors** 

Librarians

Societies

Opportunities

Reprints and e-prints

Advertising solutions

Accelerated publication

Corporate access solutions

Open access

Overview

Open journals

**Open Select** 

**Dove Medical Press** 

F1000Research

Help and information

Help and contact

Newsroom

All journals

Books

#### Keep up to date

Register to receive personalised research and resources by email















Copyright © 2024 Informa UK Limited Privacy policy Cookies Terms & conditions



Accessibility

Registered in England & Wales No. 3099067 5 Howick Place | London | SW1P 1WG

#### About Cookies On This Site



We and our partners use cookies to enhance your website experience, learn how our site is used, offer personalised features, measure the effectiveness of our services, and tailor content and ads to your interests while you navigate on the web or interact with us across devices. You can choose to accept all of these cookies or only essential cookies. To learn more or manage your preferences, click "Settings". For further information about the data we collect from you, please see our <a href="Privacy Policy">Privacy Policy</a>



Essential Onl

Settings