



118 Views | 16 CrossRef citations to date | 0 Altmetric

Original Articles

Field Application of Phenol Formaldehyde Gel in Oil Reservoir Matrix for Water Shut-off Purposes

R. Banerjee, B. Ghosh, K. Khilar, F. Boukadi & A. Bemani

Pages 1779-1787 | Published online: 13 Oct 2008

🗨️ Cite this article 🔗 <https://doi.org/10.1080/15567030701268476>

Sample our
Engineering & Technology
Journals
>> [Sign in here](#) to start your access
to the latest two volumes for 14 days

📄 Full Article

🖼️ Figures & data

📖 References

🗨️ Citations

📊 Metrics

📄 Reprints & Permissions

Read this article

🔗 Share

Abstract

A few wells from a major western India on-shore oil field are either on the verge of being shut in or have already been abandoned due to excessive water-cut (WCT) levels. Low injectivity and extreme temperatures (149°C) make it difficult for water shut-off by conventional polymer gel injection. A water-thin monomer-based in situ gelation system has been developed and successfully tried in one of the wells that ceased production due to 100% WCT. The average production of 420 barrel of oil per day (BOPD) with less than 1% WCT, in the first year of production back in 1996, has declined to less than 8 BOPD (with 98% WCT) prior to shut-in in year 2002. A rise in the oil-water contact level in combination with a coning effect was diagnosed as a possible cause of the high WCT, which was later controlled by a newly developed gelant treatment. In fact, the average post-treatment production for the first 3 months was nearly 200 BOPD. Thereafter,

production gradually stabilized in the neighborhood of 115 BOPD with a WCT of 48%. Cheap chemicals and a fast treatment method have resulted in a payback time span of 5 days and made an additional profit of U.S. \$0.6 M. The water shut-off job resulted in an impressive commercial success; technical success, however, was less than satisfactory due to the fact that, in spite of using a water-thin monomeric solution, only 40% of the designed volume could be injected due to low injectivity resulting in an abnormal pressure build-up. In addition to the gel development and treatment experiences, this article describes in detail the results of further lab investigations carried out to identify the possible reasons causing injection failure.

Keywords:

[field application](#) [gel](#) [oil reservoir](#) [phenol formaldehyde](#) [water shut-off](#)

Acknowledgments

The authors wish to thank the management of the Institute of Gas and Petroleum Technology, Panvel, New Mumbai, and the Indian Institute of Technology, Bombay, Mumbai, for providing us with the laboratory support and related field data that was used in carrying out the basic research work of this project.

Related Research Data

[Permeability Modification Using Sulfomethylated Resorcinol-Formaldehyde Gel System](#)

Source: Unknown Repository

[A Newly Developed Chromium\(III\) Gel Technology](#)

Source: SPE Reservoir Engineering

Linking provided by [ScholarSplorer](#)



Related research

Recommended articles

Cited by
16

Information for

[Authors](#)

[R&D professionals](#)

[Editors](#)

[Librarians](#)

[Societies](#)

Opportunities

[Reprints and e-prints](#)

[Advertising solutions](#)

[Accelerated publication](#)

[Corporate access solutions](#)

Open access

[Overview](#)

[Open journals](#)

[Open Select](#)

[Dove Medical Press](#)

[F1000Research](#)

Help and information

[Help and contact](#)

[Newsroom](#)

[All journals](#)

[Books](#)

Keep up to date

Register to receive personalised research and resources by email



Sign me up



Copyright © 2025 Informa UK Limited [Privacy policy](#) [Cookies](#) [Terms & conditions](#)

[Accessibility](#)



Taylor & Francis Group
an informa business

Registered in England & Wales No. 01072954
5 Howick Place | London | SW1P 1WG