

Open access

17,827 Views | 6 CrossRef citations to date | 2 Altmetric

Listen

Original Articles

Parametric CAPEX, OPEX, and LCOE expressions for offshore wind farms based on global deployment parameters

Anastasia Ioannou , Andrew Angus & Feargal Brennan

Pages 281-290 | Published online: 04 May 2018

Cite this article <https://doi.org/10.1080/15567249.2018.1461150>

Check for updates

Full Article

Figures & data

References

Citations

Metrics

Licensing

Reprints & Permissions

View PDF

ABSTRACT

We Care About Your Privacy

We and our 843 partners store and/or access information on a device, such as unique IDs in cookies to process personal data. You may accept or manage your choices by clicking below, including your right to object where legitimate interest is used, or at any time in the privacy policy page. These choices will be signaled to our partners and will not affect browsing data. [Privacy Policy](#)

We and our partners process data to provide:

Use precise geolocation data. Actively scan device characteristics for identification. Store and/or access information on a device. Personalised advertising and content, advertising and content measurement, audience research and services development.

List of Partners (vendors)

I Accept

Essential Only

Show Purpose



expressions will be particularly useful for the preliminary assessment of available deployment sites, offering cost estimates based on global decision variables.

Introduction

KEYWORDS: CAPEX LCOE nonlinear regression offshore wind farm OPEX parametric expressions

Cost model of OW farm with fixed monopile

Case study presentation and application

Results and discussion

Introduction


Conclusions

Acknowledgements

Latest targets for Europe as reported from Wind Europe aim for 320 GW of wind energy capacity to be installed by 2030, 66 GW of which is planned to come from offshore wind (OW) energy (EWEA [2015](#)). Deployment in deeper waters and further offshore is driven by the higher wind speeds, unrestricted space, and lower social impact in the marine environment (Kolios et al. [2016](#); Regueiro-Ferreira and Villasante [2016](#)), where it is estimated that the same wind turbine can produce around 50% higher power output compared to onshore. High construction costs, especially foundation and electrical connection, and limitations in operation and maintenance are key barriers that need to be overcome in order to deploy in such environments in a cost-effective way. [Figure 1](#) presents processed data from commissioned wind farms with respect to deployment depth, distance from shore, and wind farm capacity, while [Figure 2](#) shows the increase in installed wind turbine ratings from 1995 to 2017 based on data from [4C Offshore 2017](#).


Figure 1. Water depth vs. distance to shore vs. wind farm capacity.






Display full size

Figure 2. Turbine rating vs. wind farm year of commissioning.



Display tu



pertinent toward benchmarking the potential of different investment decision

alternatives.

Introduction

This article reports the development of a set of parametric models for capital

expenditure (CAPEX), operational expenditure (OPEX), and levelized cost of energy

(LCOE) as a function of a set of global variables for potential deployment sites. These

account for the wind turbine capacity (P), water depth (WD), distance from port (D), and

Results and discussion

wind farm capacity (C). These variables were selected due to their significant effect on

Conclusions

the cost-effectiveness of the investment (Shafiee et al. [2016](#)). After mapping the

Acknowledgements

multidimensional cost domain based on these variables, through a series of simulations

performed by a fully integrated and tested cost model developed by the author, results

are translated into analytical expressions to interpolate cost figures for potential wind

farms within the applicability range of the expressions. A parametric analysis and a

number of test cases illustrate the effectiveness of the models, drawing useful

conclusions.

These expressions are expected to assist investors, researchers, and other stakeholders

to undertake an initial estimate of CAPEX, OPEX, and LCOE values for OW farm projects

with varying design parameters, as well as use them as reference for estimating the

effect in the change of one of the selected design parameters. The cost model

developed incorporates the most up-to-date available parametric expressions in the

literature, while where such equations were not available, most recent data were

gathered in order to model specific costs.

Cost m

The mai

further c

cost me

the r

cycle pr

(C_1), pro

mainten

adopted

Estate 2

In this article



shed and

figure 4, the

ne model,

ved. The life-

l consent


ation and

scheme

The Crown




Figure 3. Breakdown of life-cycle costs.




Display full size

Figure 4. Integrated cost model structure.



Display full



The desi...
 survey (...)
 this stag...
 to Sh...
 life in th...
 The pro...
 acquisiti...
 system (...)

mental
 The costs of
) according
 and marine
 f data.
 owing: the
 e control
 turbine

capacity (C), while the cost of foundation as a function of the r , h , and d (Dicorato et al.

2011).

Introduction

The cost of the electric system comprises the cost of array, export and onshore cables (

Cost model of OW farm with fixed monopile

), and the cost of the substation (C_{sub}); the first, depending on the number of the wind

Case study presentation and application

turbines (N), the rotor diameter (d), and the distance from shore (D)—; the second,

Research question

depending on the number of the wind turbines, rated power of transformer (P), the

nominal voltage transformer (V), and the wind farm capacity (C) according to Dicorato et

Conclusions

al. 2011. Onshore substation cost was assumed to be half the cost of the offshore

Acknowledgements

substation. The control system cost was also taken from the same source to be equal to

75 k€/turbine.

References

Next, the installation and commissioning costs of the OW farm comprise the installation

of the wind turbine and tower (C_{tower}), foundation and transition piece (C_{ft}), scour protection (C_{scour}),

electric system (C_{elec}), and the insurance costs (C_{ins}), a categorization also used by BVGA 2010,

Dicorato et al. 2011, and Shafiee et al. 2016. The installation cost of the wind turbines

is a function of the vessel day rates (C_{vdr}), the number of vessels (workboats, heavy lift

vessels, Special Operations Vessels (SOVs), and jack up vessels; N_{v}), the duration of the

installation (T_{inst}), and the cost for the personnel ($C_{personnel}$) required for carrying out the installation.

Specifically for the installation of the wind turbines, the onshore pre-assembly method (

C_{pre}) is also expected to greatly affect the cost of installation (Sarker and Faiz 2017).

Although installation usually takes place during spring and summer time in order to

avoid adverse weather conditions, they still play an important role to activities taking

place offshore (Kaiser 2009); hence, for estimating the final installation cost of the wind

farm, a vessel day rate (C_{vdr}) is also by

other authors (Sarker and Faiz 2017).

Therefore, the total installation cost (C_{inst}) is the sum of the elements of the

wind farm (C_{tower} , C_{ft} , C_{scour} , C_{elec} , C_{ins} , C_{pre} , C_{vdr} , $C_{personnel}$) and the load capacity

and different methods.

The cost of the wind farm (C_{WF}) is the sum of the installation cost (C_{inst}) and the

repair cost (C_{rep}). The

estimation of the cost of the wind farm is the main objective of the

Netherlands (Sarker and Faiz 2017).

2011), which is the main objective of the

unplanned

ch

In this article



different severity and frequency levels, which is introduced in the software by means of a mean time to failure. The different fault type classes are classified as minor repairs, major repairs, and major replacements following the Reliawind categorization scheme (Wilkinson et al. 2019). Further data needed for the prediction of the unplanned corrective maintenance costs include the average repair times, number of required technicians, and material costs, which were adopted from Carroll et al. 2016. For the condition-based maintenance, a certain number of repairs can be set for inclusion, while the calendar-based maintenance applies to all turbines of the wind farm. For calendar-based maintenance, a yearly small maintenance operation and a longer one occurring every 5 years were considered.

Decommissioning and disposal cost of the wind farm includes the following: the removal of the wind turbine (nacelle, tower, and transition piece) as well as the balance of the plant (foundations, scour protection, cables, and substations;), the site clearance (), the onshore transportation to the disposal sites (), the port preparation (), the disposal process (), and finally the hiring vessels costs (). To accomplish this stage of the life cycle, jack-up vessels are used to transport the removed items to shore, as well as workboats to transfer personnel who will support the operation. Substations are also removed by means of a reverse installation process (with the support of a heavy lift vessel), and the jacket foundations are also cut and removed. Removal costs depend on the removal duration per turbine (), the capacity of the jack-up vessel (), the vessels' day rate (), the number of vessels (workboats, heavy lift vessels, SOVs, and jack-up vessels) (), and the cost of technicians (). As such, . The site clearance cost depends mainly on the area of the wind farm, which can be calculated by taking into account the

rotor dia... cost per...
km² (), a... d to the...
total ma... e capacity...
of truck



Case...
Key assu... ded in...
Table 1... alculat... of...
the ener... ived from

efficiency factor of 90% was assumed accounting for losses due to wake effects, cable losses, and so on. The electrical system consists of 33 kV array cables and two offshore substations of 336 MW HVAC transmission system. Additionally, the transmission assets are connected to the onshore substation by three AC export cables of 132 kV.

Case study presentation and application

Results and discussion

Table 1. Baseline specifications.



Conclusions

Display Table

Acknowledgements

References

The total undiscounted CAPEX aggregating,,, and were estimated equal to 1,698.3 M£, while the mean undiscounted annual OPEX was found around 56.3 M£/year under the baseline scenario. Nevertheless, the above figures need to be adjusted for the inflation rate and the interest rate, in order to account for the time value of money considering that the service life of an OW farm is approximately 25 years. All costs were therefore discounted and inflated with the real discount rate (r) integrating the nominal cost of capital (r_n) with the inflation rate (i), according to Fisher equation (Barro [1997](#))

(2)

where r was assumed equal to 8.81% (BVGA [2015](#)) and 2.5%. Further, the levelized cost of energy ($LCOE$), which estimates the net present value of the unit cost of electricity produced over the lifetime of the OW asset, can be calculated as

(3)

where (C_{fix})

decomm

consider

OPEX (C_{var})

well with

in 20



The para

turbine c

OPEX, C

number

×

set of complex relationships was assumed for this study based on the observation of the relationship between the input global parameters and the output variables (dCAPEX, dOPEX, and LCOE), ensuring a realistic approximation and avoiding cases of overfitting which may reduce accuracy in the results. The outcome of the finite number of scenarios that were run in order to map the cost domain is listed in Table 2, where the effect of the variable variation on CAPEX, OPEX, and LCOE can also be observed. It was shown that wind turbine and wind farm capacity have the greatest effect on CAPEX, OPEX, and LCOE. In fact, doubling the while keeping the rest of the variables stable results in 14%, 5.2%, and 5.8% decrease in the respective investment performance indicators; the corresponding effect of resulted in 77%, 92.3%, and -2.4% variation from the baseline case. The next most impactful variable on LCOE proved to be the distance from port.

Table 2. Results from the application of the model to a number of scenarios.



Display Table

Results and discussion

Based on the data presented in Table 1, which illustrate the results of the different

scenarios and) was expressing series of trends n scenarios from better m water de According equation



Abstract
Introduction
Cost model of OW farm with fixed monopile
Case study presentation and application
Results and discussion
Conclusions
Acknowledgements

Once the most appropriate regression expressions were determined, a set of overall relationships were developed for each of the dependent variables, and the nonlinear coefficients were estimated through application of the maximum likelihood method for a predetermined shape of the target equation. The analysis also returned the overall value for the regression coefficients, providing an indication on the overall quality of fit of the quantities considered. Based on the above, the following three expressions are proposed, considering the most up-to-date information and high-fidelity cost modelling structure in order to link the macro variables, namely (MW), WD (m), D (km), and (MW) to the OPEX, CAPEX, and LCOE figures.

References (4)
(5)
(6)


The R^2 for each of the expressions are 0.986, 0.999, and 0.983, respectively, denoting a satisfactory fit to the original data. Further, the data for the independent variables for the different scenarios were used as predictors using the regression coefficients, and the average value of the absolute errors that were measured in each case were 1.62%, 0.83%, and 0.82%. Finally, a series of separate test scenarios were run in order to test the performance of the model while interpolating, and the results are summarized in Table 3.

Table 3. Testing scenarios and results produced by model and parametric expressions.

Display




Following... ced and are
presente... ables to the
depen...
Figure 5... distance
from por...



References [Display full size](#)

Increase in the wind turbine rating results in an inverse exponential reduction in all three costs: CAPEX and OPEX due to the fact that less units need to be installed and maintained, and LCOE due to the reduced costs and increased expected power production. Distance from shore increases CAPEX linearly, while OPEX and LCOE increase exponentially. Increase in water depth does not affect OPEX, while it results in almost a linear increase in CAPEX and LCOE mainly due to the additional cost of the foundation and support structure as well as installation. Finally, increase in total wind farm capacity increases proportionally the amount of OPEX and CAPEX, while presents an inverse exponential reduction trend to LCOE for the given wind turbine rating due to the higher energy production and the reduced costs per wind turbine. It should be noted that the applicability range of these equations yields mainly for interpolation of



values for and lower limits in range would be introduced set of initial simulation

Con As the O farm dev different turbine In this article



high fidelity cost simulations and regressions of the results. Further, this article characterizes the effect of these variables on CAPEX, OPEX, and LCOE. It was shown that wind turbine and wind farm capacity have the greatest effect on CAPEX, OPEX, and LCOE. A future expansion of the model could potentially include more variables, so as to increase the accuracy of results, such as the interest rate which has a considerable effect on LCOE and on the discounted values of capital and operational costs. Further, the inclusion of the wind resource of the installation site could potentially improve the energy output prediction and hence, provide a better informed expression for LCOE; while the inclusion of the soil conditions, aerodynamic, and wind and wave loads at the installation site would increase the accuracy of the production and acquisition cost of the foundations and wind turbines, leading, however, to more complex relationships requiring more input data.

The high-level expressions developed in this work are expected to assist investors, researchers, and other stakeholders to derive initial estimates for wind farm projects based on global variables within the applicability range as defined above. Additionally, it should be highlighted that results from the above expressions should be treated with caution as input data have been adopted from wind farms mainly installed in North Europe, since no data currently exist for the USA or Asian OW farms.

Acknowledgments

This work was supported by grant EP/L016303/1 for Cranfield University and the

University of...
Structur...
Sciences



Refer

1. 4C Off

<http://>

Goog

2. Barro, Robert J. (1997), *Macroeconomics* (5th ed.), Cambridge: The MIT Press, United States of America, ISBN 0-262-02436-5.

Introduction

[Google Scholar](#)

Cost model of OW farm with fixed monopile

3. BEIS. 2016. Electricity generation costs. Accessed November, 2016.

Case study presentation and application

https://www.gov.uk/government/uploads/system/uploads/attachment_data/file/566567/BEIS_Electricity_Generation_Cost_Report.pdf.

Results and discussion

[Google Scholar](#)

Conclusions

[Google Scholar](#)

Acknowledgements

4. BVGA. 2010. A guide to an offshore wind farm, BVG associates on behalf of the crown estate. www.thecrownestate.co.uk/guide_to_offshore_windfarm.pdf.

References

[Google Scholar](#)

[Google Scholar](#)

5. BVGA. 2015. DECC offshore wind programme – simple levelised cost of energy model. Revision 3–26/10/2015. <http://www.demowind.eu/LCOE.xlsx>.

[Google Scholar](#)

[Google Scholar](#)

6. Carroll, J., A. McDonald, and M. David. 2016. Failure rate, repair time and unscheduled O&M cost analysis of offshore wind turbines. *Wind Energy* 19 (6):1107–19.

doi:10.1002/we.1887.

[Web of Science](#) [®] | [Google Scholar](#)

7. The Crown Estate. 2010. A guide to an offshore wind farm. London, UK.

[Google Scholar](#)

8. Dicora. 2010. Assessment of investment in offshore wind farms. *Wind Energy* 13 (4):403–51.

doi:10.1002/we.1887.



9. EWEA. 2010. European Wind Energy Association. [Google Scholar](#)

[Google Scholar](#)

[Google Scholar](#)

0. Kaiser, M. J., and B. F. Snyder. 2012. Offshore wind energy cost modeling – installation and decommissioning. London, UK: Springer-Verlag.

Introduction

[Google Scholar](#)

Cost model of OW farm with fixed monopile

1. Kaiser, M. J. 2009. The impact of weather on offshore energy losses. Energy Sources, Part B: Economics, Planning, and Policy 4 (1):59-67.

Results and discussion

doi:10.1080/15567240701421864.

Conclusions

[Web of Science ®](#) | [Google Scholar](#)

Acknowledgements

2. Kolios, A., V. Mytilinou, E. Lozano-Minguez, and K. Salonitis. 2016. A comparative study of multiple-criteria decision-making methods under stochastic inputs. Energies 9 (7):566. doi:10.3390/en9070566.

References

[Web of Science ®](#) | [Google Scholar](#)

3. Myhr, A., C. Bjerkseter, A. Ågotnes, and T. A. Nygaard. 2014. Levelised cost of energy for offshore floating wind turbines in a life cycle perspective. Renewable Energy 66:714-28. doi:10.1016/j.renene.2014.01.017.

[Web of Science ®](#) | [Google Scholar](#)

4. Regueiro-Ferreira, R. M., and S. Villasante. 2016. Recent development of offshore marine power in Galicia. Energy Sources, Part B: Economics, Planning, and Policy 11 (8):760-65. doi:10.1080/15567249.2013.787471.

[Web of Science ®](#) | [Google Scholar](#)

5. Sarker. On costs for turbine

doi:10



6. Sha. cost model for off at 21 (7):96

7. van de Pieterman, R. P., H. Braam, T. S. Obdam, L. W. M. M. Rademakers, and T. J. J.

van der Zee. 2011. Optimisation of maintenance strategies for offshore wind farms.

Introduction
The Netherlands: Energy Research Center of the Netherlands.

Cost model of OW farm with fixed monopile
[Google Scholar](#)

Case study presentation and application

8. Wilkinson, M. et al., 2010. Methodology and Results of the Reliawind Reliability Field
Results and discussion
Study; European Wind Energy Conference, Warsaw, April 2010.

Conclusions
[Google Scholar](#)

Acknowledgements

Download PDF
References

Related research

People also read

Recommended articles

Cited by
6



[Information for](#)

[Open access](#)

[Authors](#)

[Overview](#)

[R&D professionals](#)

[Open journals](#)

[Editors](#)

[Open Select](#)

[Librarians](#)

[Dove Medical Press](#)

[Societies](#)

[F1000Research](#)

[Opportunities](#)

[Help and information](#)

[Reprints and e-prints](#)

[Help and contact](#)

[Advertising solutions](#)

[Newsroom](#)

[Accelerated publication](#)

[All journals](#)

[Corporate access solutions](#)

[Books](#)

Keep up to date

Register to receive personalised research and resources by email

 [Sign me up](#)

