

Open access

21,755 Views | 954 CrossRef citations to date | 0 Altmetric

Listen

Perspective

Perspective on hetero-deformation induced (HDI) hardening and back stress

Yuntian Zhu & Xiaolei Wu

Pages 393-398 | Received 19 Apr 2019, Published online: 29 May 2019

Cite this article <https://doi.org/10.1080/21663831.2019.1616331>

Check for updates

Full Article | Figures & data | References | Citations | Metrics | Licensing

Reprints & Permissions | View PDF | View EPUB | Share

We Care About Your Privacy

We and our 887 partners store and access personal data, like browsing data or unique identifiers, on your device. Selecting I Accept enables tracking technologies to support the purposes shown under we and our partners process data to provide. Selecting Reject All or withdrawing your consent will disable them. If trackers are disabled, some content and ads you see may not be as relevant to you. You can resurface this menu to change your choices or withdraw consent at any time by clicking the Show Purposes link on the bottom of the webpage. Your choices will have effect within our Website. For more details, refer to our Privacy Policy. [Here](#)


We and our partners process data to provide:

Use precise geolocation data. Actively scan device

I Accept

Reject All

Show Purpose



IMPACT STATEMENT

The ‘back stress’ hardening in the literature can be described more accurately as hetero-deformation induced (HDI) hardening and the measured ‘back stress’ should be renamed HDI stress.


KEYWORDS:

- Heterostructured materials
- strain gradient
- back-stress
- forward stress
- hetero-deformation induced (HDI) hardening

Background

Heterostructured (HS) materials have recently attracted extensive attention from the material science community. The International Conference on Heterostructured Materials (ICHM) ‘Heterostructured Materials’ was held in March 2018 in Beijing, China. The next ICHM will be held in June 2020 in Beijing, China. The number of publications on heterostructured materials has increased significantly in recent years.





Display full size

HS materials have very diverse microstructures [1], including heterogeneous lamella structure [2], gradient structure [3-8], laminate structure [9,10], dual phase structure [11-13], harmonic structure [14-16], bi-modal structure [17-20], metal matrix composites [21-26], etc. These apparently very diverse structures have a common feature: all of them consist of both soft domains and hard domains with dramatically different

During the deformation process, the soft domains will be stretched and the hard domains will pile up and form a network structure. This network structure will be destroyed by the applied shear stress, and the hard domains will be broken into small pieces. It is longer [2,27]. When the material is deformed, the hard domains will be broken into small pieces. Since the plastic deformation is a continuous process, the hard domains will be broken into small pieces to accommodate the strain [28,29],



internal stress exerted on the matrix by precipitates. The internal stress proposed by Orowan and Fisher was later named back stress in a dislocation model by Ashby [43].

The back stress concept was later used by many groups to explain the strengthening of a metal matrix by second-phase particles in the 1970s [44-46]. More recently, back stress has been used to explain the hardening behavior and Bauschinger effect in TRIP steels [47], the transient plastic flow during creep [48], the Bauschinger effect in thin films [38], the hysteresis loop under cyclic loading [49], the extra strain hardening of HS materials [1,2,27,50,51], etc. These reports show that the back stress concept has been widely, if not fully, accepted by the materials community.

Dislocation models for back stress

Several dislocation models on the formation of back stress have been proposed [1,33,43,52-54]. The back stress is produced by geometrically necessary dislocations (GNDs). It is believed that GNDs are needed to accommodate the strain gradient in the gradient plasticity theory [28,29]. GNDs create lattice bending or misorientation, depending on their geometric pattern of arrangement. As shown in Figure 2, there are two basic types of GND arrangements. Figure 2(a) illustrates a pile-up of GNDs on a slip plane against a segment of the grain boundary, phase boundary, or domain boundary,

which is the same as the Frank-Read dislocation pile-up at the boundary and τ_a is the applied shear stress to the domain.

Figure 2(b) illustrates a boundary dislocation pile-up vertically against a boundary. (c) The mixed type of GND arrangement.



is because the HS materials have great variation in flow stress from one domain volume to the next, which makes the back-stress induced strengthening and work hardening the primary players in the mechanical behavior. For example, an HS lamella Ti was found to have the strength of the ultrafine-grained Ti and uniform elongation higher than that of the coarse-grained Ti [2]. In addition, it also has strain hardening that is higher than the coarse-grained Ti. These mechanical behaviors cannot be explained by the conventional mechanisms in the textbooks. Therefore, back stress strengthening and work hardening have been used to explain the extraordinary mechanical properties of HS materials [1,2,27,60].

Issues with the back stress concept

As discussed above, back stress strengthening and work hardening have been believed responsible for the superior combination of strength and ductility of HS materials [1,2,39,61] as well as the Bauschinger effect [36,38,47,50]. With the fast development of the field of HS materials, it is of critical importance to clarify and understand how the back stress affects the mechanical behavior. Specifically, methods and equations have been proposed and developed to experimentally measure back stress from mechanical testing. Most of these methods and equations are not well anchored in deformation

physics, and if the measured materials. To analyze the HS domain boundary in the soft dislocation pileup work hardening stress in the soft phase is a stress concentration which is in the same stress. In other words, the hard domain, which in Figure 3. turn indu



Outstanding issues

The definitions of HDI hardening and HDI stress raise some scientific issues for future study. First, the back stress and forward stress are coupled and act in opposite directions. It is not clear how they interact with each other to produce the HDI hardening and HDI stress. Recently, it has been observed that local shear bands are formed across domain boundaries [62]. This might be caused by local interactions between local back stresses and forward stresses. Second, the HDI stress (measured 'back stress' in the literature [2,27]) appears to increase quickly in the elastic-plastic deformation stage, but slows down during the plastic deformation stage, which need to be investigated. Third, GND pile-ups lead to the development of back stress, which in turn induces forward stress. It is also believed that GNDs are needed to accommodate strain gradient near domain boundaries. The relationships among back stress, forward stress, strain gradient and HDI stress need to be studied. Understanding these issues will help us with understanding the fundamental physics as well as the heterostructure-mechanical properties of HS materials.

Disclosure statement

No potential conflicts of interest were reported by the authors.

Refer

1. Wu XL

un

10.1








2. Wu XL

grain s

14505





3. Lu K. Making strong nanomaterials ductile with gradients. *Science*. 2014;345:1455-1456. doi: 10.1126/science.1255940
 | [PubMed](#) | [Web of Science ®](#) | [Google Scholar](#)
4. Wu XL, Jiang P, Chen L, et al. Extraordinary strain hardening by gradient structure. *Proc Natl Acad Sci USA*. 2014;111:7197-7201. doi: 10.1073/pnas.1324069111
 | [PubMed](#) | [Web of Science ®](#) | [Google Scholar](#)
5. Wu XL, Jiang P, Chen L, et al. Synergetic strengthening by gradient structure. *Mater Res Lett*. 2014;2:185-191. doi: 10.1080/21663831.2014.935821
 | [Web of Science ®](#) | [Google Scholar](#)
6. Fang TH, Li WL, Tao NR, et al. Revealing extraordinary intrinsic tensile plasticity in gradient nano-grained copper. *Science*. 2011;331:1587-1590. doi: 10.1126/science.1200177
 | [PubMed](#) | [Web of Science ®](#) | [Google Scholar](#)
7. Chen AY, Liu JB, Wang HT, et al. Gradient twinned 304 stainless steels for high strength and high ductility. *Mater Sci Eng A*. 2016;667:179-188. doi: 10.1016/j.msea.2016.04.070



8. Wei YJ, et al. Gradient structure in steel through...

9. Ma YH, et al. Gradient laminates: role of...


10. Beyer M, et al. Gradient structure under extreme...





1. Calcagnotto M, Adachi Y, Ponge D, et al. Deformation and fracture mechanisms in fine- and ultrafine-grained ferrite/martensite dual-phase steels and the effect of aging. *Acta Mater.* 2011;59:658–670. doi: 10.1016/j.actamat.2010.10.002
 | [Web of Science ®](#) | [Google Scholar](#)

2. Li ZM, Pradeep KG, Deng Y, et al. Metastable high-entropy dual-phase alloys overcome the strength-ductility trade-off. *Nature.* 2016;534:227. doi: 10.1038/nature17981
 | [PubMed](#) | [Web of Science ®](#) | [Google Scholar](#)


3. Park K, Nishiyama M, Nakada N, et al. Effect of the martensite distribution on the strain hardening and ductile fracture behaviors in dual-phase steel. *Mater Sci Eng A.* 2014;604:135–141. doi: 10.1016/j.msea.2014.02.058
 | [Web of Science ®](#) | [Google Scholar](#)





4. Sawangrat C, Kato S, Orlov D, et al. Harmonic-structured copper: performance and proof of fabrication concept based on severe plastic deformation of powders. *J Mater Sci.* 2014;49:6579–6585. doi: 10.1007/s10853-014-8258-4
 | [Web of Science ®](#) | [Google Scholar](#)


5. Zhang [unclear] in SUS304L
steel t [unclear]
2014; [unclear]
 | [Web of Science ®](#) | [Google Scholar](#)

6. Vajpai [unclear] Ti-6Al-4V
alloy v [unclear]
Ma [unclear] ion. Metall

7. Wang [unclear] ured metal.
Nature



8. Han BQ, Huang JY, Zhu YT, et al. Strain rate dependence of properties of cryomilled bimodal 5083 Al alloys. *Acta Mater.* 2006;54:3015–3024. doi: 10.1016/j.actamat.2006.02.045
 | [Web of Science ®](#) | [Google Scholar](#)
9. Han BQ, Lee Z, Witkin D, et al. Deformation behavior of bimodal nanostructured 5083 Al alloys. *Metall Mater Trans A.* 2005;36a:957–965. doi: 10.1007/s11661-005-0289-7
 | [Web of Science ®](#) | [Google Scholar](#)
10. Zhao YH, Topping T, Bingert JF, et al. High tensile ductility and strength in bulk nanostructured nickel. *Adv Mater.* 2008;20:3028–3033. doi: 10.1002/adma.200800214
 | [Web of Science ®](#) | [Google Scholar](#)
11. Liu J, Chen Z, Zhang FG, et al. Simultaneously increasing strength and ductility of nanoparticles reinforced Al composites via accumulative orthogonal extrusion process. *Mater Res Lett.* 2018;6:406–412. doi: 10.1080/21663831.2018.1471421
 | [Web of Science ®](#) | [Google Scholar](#)

12. Zhao L, Guo Q, Li Z, et al. Grain boundary-assisted deformation in graphene-Al nanolaminate. *Acta Mater.* 2018;157:105–114. doi: 10.1016/j.actamat.2018.05.011
 | [Web of Science ®](#) | [Google Scholar](#)

13. Choudhury S, Ghosh S, Ghosh B, et al. Grain boundary-assisted deformation in B2 precipitates reinforced Al matrix. *Mater Res Lett.* 2018;6:406–412. doi: 10.1080/21663831.2018.1471421
 | [Web of Science ®](#) | [Google Scholar](#)

14. Llorca A, Llorca A, Llorca A, et al. Grain boundary-assisted deformation in Al matrix reinforced metal-organic frameworks. *Acta Mater.* 2018;157:105–114. doi: 10.1016/j.actamat.2018.05.011
 | [Web of Science ®](#) | [Google Scholar](#)



25. Thilly L, Van Petegem S, Renault PO, et al. A new criterion for elasto-plastic transition in nanomaterials: application to size and composite effects on Cu-Nb nanocomposite wires. *Acta Mater.* 2009;57:3157–3169. doi: 10.1016/j.actamat.2009.03.021

 | [Web of Science](#)® | [Google Scholar](#)

26. Tanaka K, Mori T. Hardening of crystals by non-deforming particles and fibres. *Acta Metall.* 1970;18:931. doi: 10.1016/0001-6160(70)90020-9

 | [Google Scholar](#)

27. Yang MX, Pan Y, Yuan FP, et al. Back stress strengthening and strain hardening in gradient structure. *Mater Res Lett.* 2016;4:145–151. doi: 10.1080/21663831.2016.1153004

 | [Web of Science](#)® | [Google Scholar](#)

28. Gao HJ, Huang YG. Geometrically necessary dislocation and size-dependent plasticity. *Scripta Mater.* 2003;48:113–118. doi: 10.1016/S1359-6462(02)00329-9

 | [Web of Science](#)® | [Google Scholar](#)

29. Ashby MF. Deformation of plastically non-homogeneous materials. *Philos Mag.* 1970;21:399. doi: 10.1080/14786437008238426

30. Feaugoien J, et al. Mechanical properties of SI 316 L at 300 K. doi: 10.1016/j.actamat.2009.03.021

31. Ku, et al. Back stress and strain hardening in gradient structure. *Mater Res Lett.* 1979;1:105–110.

32. Bate P, et al. *Acta Mater.* 2009;57:1097–1105.



33. Gibeling JC, Nix WD. A numerical study of long-range internal-stresses associated with subgrain boundaries. *Acta Metall.* 1980;28:1743-1752. doi: 10.1016/0001-6160(80)90027-9

 | [Google Scholar](#)

34. Levine LE, Geantil P, Larson BC, et al. Disordered long-range internal stresses in deformed copper and the mechanisms underlying plastic deformation. *Acta Mater.* 2011;59:5803-5811. doi: 10.1016/j.actamat.2011.05.056

 | [Web of Science ®](#) | [Google Scholar](#)

35. Phan TQ, Levine LE, Lee IF, et al. Synchrotron X-ray microbeam diffraction measurements of full elastic long range internal strain and stress tensors in commercial-purity aluminum processed by multiple passes of equal-channel angular pressing. *Acta Mater.* 2016;112:231-241. doi: 10.1016/j.actamat.2016.04.035

 | [Web of Science ®](#) | [Google Scholar](#)

36. Liu XL, Yuan FP, Zhu YT, et al. Extraordinary Bauschinger effect in gradient structured copper. *Scr Mater.* 2018;150:57-60. doi: 10.1016/j.scriptamat.2018.03.007

 | [Web of Science ®](#) | [Google Scholar](#)

37. Momp...
motion...
2012;...
e dislocation

38. Xiang...
2006;...
a Mater.

39. Taya M...
alumin...
5093(...
c-6061
0921-



40. Bauschinger J. Über die Veränderung der Elasticitätsgrenze und der Festigkeit des Eisens und Stahls durch Strecken und Quetschen, durch Erwärmen und Abkühlen und durch oftmal wiederholte Beanspruchung. Mitteilungen aus dem mechanisch-technischen Laboratorium der k. polytechnischen Schule. München. 1886;13:1-115.
[Google Scholar](#)

41. Orowan E. Classification and nomenclature of internal stresses. J Inst Met. 1947;73:47-59.
[Google Scholar](#)

42. Fisher JC, Hart EW, Pry RH. The hardening of metal crystals by precipitate particles. Acta Metall. 1953;1:336-339. doi: 10.1016/0001-6160(53)90109-6
[Google Scholar](#)

43. Ashby MF. Work hardening of dispersion-hardened crystals. Philos Mag. 1966;14:1157-1178. doi: 10.1080/14786436608224282
[Web of Science](#) [®] | [Google Scholar](#)

44. Tanaka K, Mori T. Hardening of crystals by non-deforming particles and fibres. Acta Metall. 1970;18:931. doi: 10.1016/0001-6160(70)90020-9

45. Mori T. Hardening of materials with non-deforming particles. Acta Metall. 1970;18:931. doi: 10.1016/0001-6160(70)90020-9

46. Brinell O. The Brinell hardness test. J Res Natl Stand. 1975;78:17-31.

47. Kato H. The Bauschinger effect in metals. J Appl Phys. 1954;25:1023-1028. doi: 10.2307/3349777



8. Gan W, Zhang PH, Wagoner RH, et al. Effect of load redistribution in transient plastic flow. Metall Mater Trans A. 2006;37a:2097-2106. doi: 10.1007/BF02586130

 | [Web of Science ®](#) | [Google Scholar](#)

9. Fournier B, Sauzay M, Caes C, et al. Analysis of the hysteresis loops of a martensitic steel - Part II: study of the influence of creep and stress relaxation holding times on cyclic behaviour. Mater Sci Eng A. 2006;437:197-211. doi: 10.1016/j.msea.2006.08.087

 | [Web of Science ®](#) | [Google Scholar](#)

10. Hu XZ, Jin SB, Zhou H, et al. Bauschinger effect and back stress in gradient Cu-Ge alloy. Metall Mater Trans A. 2017;48a:3943-3950. doi: 10.1007/s11661-017-4176-9

 | [Web of Science ®](#) | [Google Scholar](#)

11. Yuan FP, Yan DS, Sun JD, et al. Ductility by shear band delocalization in the nano-layer of gradient structure. Mater Res Lett. 2019;7:12-17. doi: 10.1080/21663831.2018.1546238

 | [Web of Science ®](#) | [Google Scholar](#)

12. Mughrabi H. On the role of strain gradients and long-range internal stresses in the compo . doi: 10.10



13. Mughrabi H. On the role of strain gradients and long-range internal stresses in the compo . doi: 10.10
deform . doi: 10.10
A. 200



14. Jennin . doi: 10.10
Bausc . doi: 10.10
2012;

55. Hughes DA, Hansen N, Bammann DJ. Geometrically necessary boundaries, incidental dislocation boundaries and geometrically necessary dislocations. *Scripta Mater.* 2003;48:147-153. doi: 10.1016/S1359-6462(02)00358-5

 | [Web of Science®](#) | [Google Scholar](#)

56. Hull D, Bacon DJ. *Introduction to dislocations*. 3rd ed. Oxford: Pergamon Press; 1984.

[Google Scholar](#)

57. Hirth JP, Lothe J. *Theory of dislocations*. 2nd ed. Malabar (FL): Krieger Publishing Company; 1992.

[Google Scholar](#)

58. Hertzberg RW. *Deformation and fracture mechanics of engineering materials*. 3rd ed. New York: Wiley; 1989.

[Google Scholar](#)

59. Kassner ME, Geantil P, Levine LE. Long range internal stresses in single-phase crystalline materials. *Intl J Plasticity*. 2013;45:44-60. doi: 10.1016/j.ijplas.2012.10.003

 | [Web of Science®](#) | [Google Scholar](#)

60. Ma XL
grain/
10.10

61. Xu R
na
10.10



62. Huang
ductili
10.10

Related research

People also read

Recommended articles

Cited by
954

Synergetic Strengthening by Gradient Structure >

X. L. Wu et al.

Materials Research Letters

Published online: 2 Jul 2014



The deformation of plastically non-homogeneous materials >

M. F. Ashby

The Philosophical Magazine: A Journal of Theoretical Experimental and Applied Physics

Published online: 13 Sep 2006

Additional hardening in harmonic structured materials by strain partitioning and back stress >

Hyung Keun Park et al.

Material

Publishe



Information for

- Authors
- R&D professionals
- Editors
- Librarians
- Societies

Opportunities

- Reprints and e-prints
- Advertising solutions
- Accelerated publication
- Corporate access solutions

Keep up to date

Register to receive personalised research and resources by email

 Sign me up



Open access

- Overview
- Open journals
- Open Select
- Dove Medical Press
- F1000Research
- Help and information
- Help and contact
- Newsroom
- All journals
- Books

Copyright © 2024 Taylor & Francis Group, an informa business

Accessib

Registered
5 Howick Pl

