

Open access

17,202 Views

569 CrossRef citations to date

0 Altmetric

Listen

Perspective

Perspective on hetero-deformation induced (HDI) hardening and back stress

Yuntian Zhu & Xiaolei Wu

Pages 393-398 | Received 19 Apr 2019, Published online: 29 May 2019

Cite this article <https://doi.org/10.1080/21663831.2019.1616331>

Check for updates

Full Article

Figures & data

References

Citations

Metrics

Licensing

Reprints & Permissions

View PDF

View EPUB

ABSTRACT

Heterostructured materials have been reported as a new class of materials with superior mechanical properties, which was attributed to the development of back stress. T

We Care About Your Privacy

We and our 842 partners store and/or access information on a device, such as unique IDs in cookies to process personal data. You may accept or manage your choices by clicking below, including your right to object where legitimate interest is used, or at any time in the privacy policy page. These choices will be signaled to our partners and will not affect browsing data. [Privacy Policy](#)

We and our partners process data to provide:

Use precise geolocation data. Actively scan device characteristics for identification. Store and/or access information on a device. Personalised advertising and content, advertising and content measurement, audience research and services development.


List of Partners (vendors)

I Accept

Essential Only

Show Purpose





IMPACT STATEMENT


The ‘back stress’ hardening in the literature can be described more accurately as hetero-deformation induced (HDI) hardening and the measured ‘back stress’ should be renamed HDI stress.

KEYWORDS: [Heterostructured materials](#) [strain gradient](#) [back-stress](#) [forward stress](#)
[hetero-deformation induced \(HDI\) hardening](#)

Background

Heterostructured (HS) materials have recently attracted extensive attention from the materials community, as evidenced by the increasing number of international conferences and publications in recent years. For example, a symposium entitled ‘Heterogeneous and Gradient Materials III’ was held in the TMS Annual meeting in March 2019. A Gordon Research Conference on Heterostructured Materials will be held in June 2019. A symposium on Nanostructured, Heterostructured & Gradient Materials will be held in the Chinese Materials Conference in July 2019. Figure 1 shows that the number of publications related to HS materials has increased significantly in recent years.






Display full size

HS materials have very diverse microstructures [1], including heterogeneous lamella structure [2], gradient structure [3-8], laminate structure [9,10], dual phase structure [11-13], harmonic structure [14-16], bi-modal structure [17-20], metal matrix composites [21-26], etc. These apparently very diverse structures have a common feature: all of them consist of both soft domains and hard domains with dramatically different flow stresses (or strength) [1].

During tensile deformation of HS materials, the soft domains will start plastic deformation first. As the deformation progresses, the hard domains will start to pile up and the plastic deformation will be localized in the soft domains. The stress, in the hard domains, will increase and the plastic deformation will be sustained in the hard domains. The plastic deformation will continue to propagate in the hard domains and the strain will be accommodated by the hard domains [28,29],



which in turn produces back-stress induced hardening, which helps with retaining ductility [1,2].

As described above, back stress is believed responsible for the strengthening and extra strain hardening observed in HS materials. Furthermore, various schemes to measure back stress from mechanical testing have been proposed [27,30,31], most equations for calculating back stress are based on concepts and assumptions instead of fundamental dislocation-based derivations. Back stress is also often associated with kinematic hardening, a term extensively used in the field of mechanics [32], which describes the mechanical phenomenon without addressing its physical origin. The concept and term of back stress are themselves still under debate in the materials community, with some researchers prefer to call them long-range internal stress [33,34]. Although back stress is usually small in homogeneous metals [27,35], it becomes significant for HS materials [1,2]. Therefore, it is of critical importance to understand the relationship between back stress and the mechanical behavior of HS materials.


In this perspective, we will briefly delineate the history of back stress, analyzing the development of back stress and forward stress in HS materials. We will show the inadequacy of using back stress to describe the strengthening and extra strain hardening in HS materials. In addition, back stress cannot be measured from mechanical testing, and the back-stress reported in the literature can be more accurately described as hetero-deformation induced (HDI) stress. We'll also briefly discuss the current fundamental issues that need to be investigated.

Brief h

In the fo
compreh
they
alloy wa
lower th
referred
pile-up a
following

instead of a
t because
t after an
strength
has been
slocation
slip of
of a





Display full size

Under the forward stress, the hard domain may behave in three different ways. Note that the forward stress in the hard domain near the domain boundary can be many times higher than the applied stress. First, if the hard domain is not much stronger than the soft domain, the leading dislocation at the head of a pile-up may be pushed into the domain boundary, which may lead to the emission of another dislocation from the boundary into the hard domain. In such a scenario, the buildup of back stress and forward stress is limited, and their influence on the mechanical behavior is also limited, as in the case of GND pile-ups at grain boundaries in conventional homogeneous materials. Second, if the hard domains are much stronger than the soft domains, the domain boundary will be much more effective in blocking GNDs, and the hard domain will remain elastic until the back stress is very high in the soft domain. This will increase the global yield stress and result in extra work hardening when both domains are deforming plastically, especially when the soft domain is fully constrained by the hard domain, as reported in the heterogeneous lamella Ti [21]. Third, if the hard domain is not

plastically deformed by second phase particles, the yield strength is too high, and the hard domain is the case. As dislocations pile up at the boundary, the hard domain (or soft domain) will be weaker if it is deformed. The mechanical behavior is determined by the unique microstructure of the materials. This

Outstanding issues

The definitions of HDI hardening and HDI stress raise some scientific issues for future study. First, the back stress and forward stress are coupled and act in opposite directions. It is not clear how they interact with each other to produce the HDI hardening and HDI stress. Recently, it has been observed that local shear bands are formed across domain boundaries [62]. This might be caused by local interactions between local back stresses and forward stresses. Second, the HDI stress (measured 'back stress' in the literature [2,27]) appears to increase quickly in the elastic-plastic deformation stage, but slows down during the plastic deformation stage, which need to be investigated. Third, GND pile-ups lead to the development of back stress, which in turn induces forward stress. It is also believed that GNDs are needed to accommodate strain gradient near domain boundaries. The relationships among back stress, forward stress, strain gradient and HDI stress need to be studied. Understanding these issues will help us with understanding the fundamental physics as well as the heterostructure-mechanical properties of HS materials.

Disclosure statement

No potential conflict of interest was reported by the authors.

Refer

1. Wu XL

unpre

10.7










2. Wu XL






grain s

14505



3. Lu K. Making strong nanomaterials ductile with gradients. *Science*. 2014;**345**:1455–1456. doi: 10.1126/science.1255940
 | [PubMed](#) | [Web of Science ®](#) | [Google Scholar](#)
4. Wu XL, Jiang P, Chen L, et al. Extraordinary strain hardening by gradient structure. *Proc Natl Acad Sci USA*. 2014;**111**:7197–7201. doi: 10.1073/pnas.1324069111
 | [PubMed](#) | [Web of Science ®](#) | [Google Scholar](#)
5. Wu XL, Jiang P, Chen L, et al. Synergetic strengthening by gradient structure. *Mater Res Lett*. 2014;**2**:185–191. doi: 10.1080/21663831.2014.935821
 | [Web of Science ®](#) | [Google Scholar](#)
6. Fang TH, Li WL, Tao NR, et al. Revealing extraordinary intrinsic tensile plasticity in gradient nano-grained copper. *Science*. 2011;**331**:1587–1590. doi: 10.1126/science.1200177
 | [PubMed](#) | [Web of Science ®](#) | [Google Scholar](#)
7. Chen AY, Liu JB, Wang HT, et al. Gradient twinned 304 stainless steels for high strength and high ductility. *Mater Sci Eng A*. 2016;**667**:179–188. doi: 10.1016/j.msea.2016.04.070
 | [Web of Science ®](#) | [Google Scholar](#)
8. Wei YJ, Li YO, Zhu LC, et al. Evading the strength- ductility trade-off dilemma in steel through

9. Ma XL, et al. The role of
 laminates: 5.06.023
10. Beyer, et al. Under
extreme
10.10








1. Calcagnotto M, Adachi Y, Ponge D, et al. Deformation and fracture mechanisms in fine- and ultrafine-grained ferrite/martensite dual-phase steels and the effect of aging. *Acta Mater.* 2011;**59**:658–670. doi: 10.1016/j.actamat.2010.10.002
 | [Web of Science ®](#) | [Google Scholar](#)
2. Li ZM, Pradeep KG, Deng Y, et al. Metastable high-entropy dual-phase alloys overcome the strength-ductility trade-off. *Nature.* 2016;**534**:227. doi: 10.1038/nature17981
 | [PubMed](#) | [Web of Science ®](#) | [Google Scholar](#)
3. Park K, Nishiyama M, Nakada N, et al. Effect of the martensite distribution on the strain hardening and ductile fracture behaviors in dual-phase steel. *Mater Sci Eng A.* 2014;**604**:135–141. doi: 10.1016/j.msea.2014.02.058
 | [Web of Science ®](#) | [Google Scholar](#)
4. Sawangrat C, Kato S, Orlov D, et al. Harmonic-structured copper: performance and proof of fabrication concept based on severe plastic deformation of powders. *J Mater Sci.* 2014;**49**:6579–6585. doi: 10.1007/s10853-014-8258-4
 | [Web of Science ®](#) | [Google Scholar](#)
5. Zhang Z, Vajpai SK, Orlov D, et al. Improvement of mechanical properties in SUS304L steel through the control of bimodal microstructure characteristics. *Mater Sci Eng A.* 2014;**598**:106–113. doi: 10.1016/j.msea.2014.01.023


6. Vajpai SK, Orlov D, et al. Improvement of mechanical properties in Ti-6Al-4V alloy via severe plastic deformation. *Metall Mater Trans A.* 2014;**45**:1000–1005. doi: 10.1007/s11661-014-2300-4

7. Wang Y, et al. Severe plastic deformation of metal. *Nature Mater.* 2014;**13**:104–112. doi: 10.1038/nmat3841



8. Han BQ, Huang JY, Zhu YT, et al. Strain rate dependence of properties of cryomilled bimodal 5083 Al alloys. *Acta Mater.* 2006;**54**:3015–3024. doi: 10.1016/j.actamat.2006.02.045
 | [Web of Science ®](#) | [Google Scholar](#)
9. Han BQ, Lee Z, Witkin D, et al. Deformation behavior of bimodal nanostructured 5083 Al alloys. *Metall Mater Trans A.* 2005;**36a**:957–965. doi: 10.1007/s11661-005-0289-7
 | [Web of Science ®](#) | [Google Scholar](#)
10. Zhao YH, Topping T, Bingert JF, et al. High tensile ductility and strength in bulk nanostructured nickel. *Adv Mater.* 2008;**20**:3028–3033. doi: 10.1002/adma.200800214
 | [Web of Science ®](#) | [Google Scholar](#)
11. Liu J, Chen Z, Zhang FG, et al. Simultaneously increasing strength and ductility of nanoparticles reinforced Al composites via accumulative orthogonal extrusion process. *Mater Res Lett.* 2018;**6**:406–412. doi: 10.1080/21663831.2018.1471421
 | [Web of Science ®](#) | [Google Scholar](#)
12. Zhao L, Guo Q, Li Z, et al. Grain boundary-assisted deformation in graphene-Al nanolaminated composite micro-pillars. *Mater Res Lett.* 2018;**6**:41–48. doi: 10.1080/21663831.2017.1386241
 | [Web of Science ®](#) | [Google Scholar](#)

13. Choudhury S, et al. B2 precipitates in Al-Mg alloy. *Mater Res Lett.* 2018;**6**:41–48. doi: 10.1080/21663831.2017.1386241
 | [Web of Science ®](#) | [Google Scholar](#)
14. Llorca A, et al. Strengthened metal-matrix composites. *Acta Mater.* 2016;**116**:716X(1)–716X(12). doi: 10.1016/j.actamat.2016.09.056
 | [Web of Science ®](#) | [Google Scholar](#)



25. Thilly L, Van Petegem S, Renault PO, et al. A new criterion for elasto-plastic transition in nanomaterials: application to size and composite effects on Cu-Nb nanocomposite wires. *Acta Mater.* 2009;**57**:3157–3169. doi: 10.1016/j.actamat.2009.03.021

 | [Web of Science](#)® | [Google Scholar](#)

26. Tanaka K, Mori T. Hardening of crystals by non-deforming particles and fibres. *Acta Metall.* 1970;**18**:931. doi: 10.1016/0001-6160(70)90020-9

 | [Google Scholar](#)

27. Yang MX, Pan Y, Yuan FP, et al. Back stress strengthening and strain hardening in gradient structure. *Mater Res Lett.* 2016;**4**:145–151. doi: 10.1080/21663831.2016.1153004

 | [Web of Science](#)® | [Google Scholar](#)

28. Gao HJ, Huang YG. Geometrically necessary dislocation and size-dependent plasticity. *Scripta Mater.* 2003;**48**:113–118. doi: 10.1016/S1359-6462(02)00329-9

 | [Web of Science](#)® | [Google Scholar](#)

29. Ashby MF. Deformation of plastically non-homogeneous materials. *Philos Mag.* 1970;**21**:399. doi: 10.1080/14786437008238426

 | [Web of Science](#)® | [Google Scholar](#)

30. Feaugas X. On the origin of the tensile flow stress in the stainless steel AISI 316 L at 300 K. doi: 10.1016/j.actamat.2009.03.021



31. Kuhlmann B. Back stress and strain hardening in nanocrystalline copper. *Acta Mater.* 1997;**45**:1105–1115. doi: 10.1016/S1359-6462(97)00110-5



32. Bate MR. The effect of grain size on the tensile flow stress of copper. *Acta Mater.* 1997;**45**:1105–1115. doi: 10.1016/S1359-6462(97)00110-5

33. Gibeling JC, Nix WD. A numerical study of long-range internal-stresses associated with subgrain boundaries. *Acta Metall.* 1980;**28**:1743–1752. doi: 10.1016/0001-6160(80)90027-9

 | [Google Scholar](#)

34. Levine LE, Geantil P, Larson BC, et al. Disordered long-range internal stresses in deformed copper and the mechanisms underlying plastic deformation. *Acta Mater.* 2011;**59**:5803–5811. doi: 10.1016/j.actamat.2011.05.056

 | [Web of Science ®](#) | [Google Scholar](#)

35. Phan TQ, Levine LE, Lee IF, et al. Synchrotron X-ray microbeam diffraction measurements of full elastic long range internal strain and stress tensors in commercial-purity aluminum processed by multiple passes of equal-channel angular pressing. *Acta Mater.* 2016;**112**:231–241. doi: 10.1016/j.actamat.2016.04.035

 | [Web of Science ®](#) | [Google Scholar](#)

36. Liu XL, Yuan FP, Zhu YT, et al. Extraordinary Bauschinger effect in gradient structured copper. *Scr Mater.* 2018;**150**:57–60. doi: 10.1016/j.scriptamat.2018.03.007

 | [Web of Science ®](#) | [Google Scholar](#)

37. Momprou F, Caillard D, Legros M, et al. In situ TEM observations of reverse dislocation motion upon unloading in tensile-deformed UFG aluminium. *Acta Mater.* 2012;**60**:3402–3414. doi: 10.1016/j.actamat.2012.02.049

38. Xiang *Acta Mater.* 2006;

39. Taye *Acta Mater.* c-6061 0921-5093(


40. Bauschinger J. Über die Veränderung der Elasticitätsgrenze und der Festigkeit des Eisens und Stahls durch Strecken und Quetschen, durch Erwärmen und Abkühlen und durch oftmal wiederholte Beanspruchung. Mitteilungen aus dem mechanisch-technischen Laboratorium der k. polytechnischen Schule. München. 1886;13:1-115.
[Google Scholar](#)

41. Orowan E. Classification and nomenclature of internal stresses. J Inst Met. 1947;73:47-59.
[Google Scholar](#)

42. Fisher JC, Hart EW, Pry RH. The hardening of metal crystals by precipitate particles. Acta Metall. 1953;1:336-339. doi: 10.1016/0001-6160(53)90109-6
[Google Scholar](#)

43. Ashby MF. Work hardening of dispersion-hardened crystals. Philos Mag. 1966;14:1157-1178. doi: 10.1080/14786436608224282
[Web of Science ®](#) | [Google Scholar](#)

44. Tanaka K, Mori T. Hardening of crystals by non-deforming particles and fibres. Acta Metall. 1970;18:931. doi: 10.1016/0001-6160(70)90020-9
[Google Scholar](#)

45. Mori T, Tanaka K. Average stress in matrix and average elastic energy of materials with n... 01-6160(

46. Brown... ll. 197...


47. Kato H... auschinger effect... i: 10.23...

8. Gan W, Zhang PH, Wagoner RH, et al. Effect of load redistribution in transient plastic flow. *Metall Mater Trans A*. 2006;**37a**:2097–2106. doi: 10.1007/BF02586130

 | [Web of Science ®](#) | [Google Scholar](#)

9. Fournier B, Sauzay M, Caes C, et al. Analysis of the hysteresis loops of a martensitic steel - Part II: study of the influence of creep and stress relaxation holding times on cyclic behaviour. *Mater Sci Eng A*. 2006;**437**:197–211. doi: 10.1016/j.msea.2006.08.087

 | [Web of Science ®](#) | [Google Scholar](#)

10. Hu XZ, Jin SB, Zhou H, et al. Bauschinger effect and back stress in gradient Cu-Ge alloy. *Metall Mater Trans A*. 2017;**48a**:3943–3950. doi: 10.1007/s11661-017-4176-9

 | [Web of Science ®](#) | [Google Scholar](#)

11. Yuan FP, Yan DS, Sun JD, et al. Ductility by shear band delocalization in the nano-layer of gradient structure. *Mater Res Lett*. 2019;**7**:12–17. doi: 10.1080/21663831.2018.1546238

 | [Web of Science ®](#) | [Google Scholar](#)

12. Mughrabi H. On the role of strain gradients and long-range internal stresses in the composite model of crystal plasticity. *Mater Sci Eng A*. 2001;**317**:171–180. doi: 10.1016/S0921-5093(01)01173-X

 | [Web of Science ®](#) | [Google Scholar](#)

13. Mughrabi H. On the role of strain gradients and long-range internal stresses in the composite model of crystal plasticity. *Mater Sci Eng A*. 2001;**317**:171–180. doi: 10.1016/S0921-5093(01)01173-X

14. Jenks E, Mughrabi H, Bauschinger W, et al. Bauschinger effect and back stress in gradient Cu-Ge alloy. *Metall Mater Trans A*. 2012;**43a**:3943–3950. doi: 10.1007/s11661-012-1176-9



55. Hughes DA, Hansen N, Bammann DJ. Geometrically necessary boundaries, incidental dislocation boundaries and geometrically necessary dislocations. *Scripta Mater.* 2003;**48**:147–153. doi: 10.1016/S1359-6462(02)00358-5

 | [Web of Science®](#) | [Google Scholar](#)

56. Hull D, Bacon DJ. *Introduction to dislocations*. 3rd ed. Oxford: Pergamon Press; 1984.
[Google Scholar](#)

57. Hirth JP, Lothe J. *Theory of dislocations*. 2nd ed. Malabar (FL): Krieger Publishing Company; 1992.
[Google Scholar](#)

58. Hertzberg RW. *Deformation and fracture mechanics of engineering materials*. 3rd ed. New York: Wiley; 1989.
[Google Scholar](#)

59. Kassner ME, Geantil P, Levine LE. Long range internal stresses in single-phase crystalline materials. *Intl J Plasticity*. 2013;**45**:44–60. doi: 10.1016/j.ijplas.2012.10.003

 | [Web of Science®](#) | [Google Scholar](#)

60. Ma XL, Huang CX, Xu WZ, et al. Strain hardening and ductility in a coarse-grain/nanostructure laminate material. *Scripta Mater.* 2015;**103**:57–60. doi: 10.1016/j.scripta.2015.07.011

61. Xu R, et al. Strain hardening and ductility in a coarse-grain/nanostructure laminate material. *Scripta Mater.* 2015;**103**:57–60. doi: 10.1016/j.scripta.2015.07.011



62. Huang CX, et al. Strain hardening and ductility in a coarse-grain/nanostructure laminate material. *Scripta Mater.* 2015;**103**:57–60. doi: 10.1016/j.scripta.2015.07.011

Related research

People also read

Recommended articles

Cited by
569

Information for

Authors

R&D professionals

Editors

Librarians

Societies

Opportunities

Reprints and e-prints

Advertising solutions

Accelerated publication

Corporate access solutions

Open access

Overview

Open journals

Open Select

Dove Medical Press

F1000Research

Help and information

Help and contact

Newsroom

All journals

Books

Keep up to date

Register to receive updates
by email



Sign up



Copyright

Accessibility

Registered
5 Howick Place



Wiley & Francis Group
Wiley Informa business