







Q

Home ► All Journals ► Engineering & Technology ► Petroleum Science and Technology ► List of Issues ► Volume 20, Issue 9-10 ► MANAGEMENT OF OIL SANDS TAILINGS

Petroleum Science and Technology >

Volume 20, 2002 - <u>Issue 9-10</u>

3,479 150 59

Views CrossRef citations to date Altmetric

Original Articles

## MANAGEMENT OF OIL SANDS TAILINGS

Richard J. Chalaturnyk, J. Don Scott & Baki Özüm 🔀

Pages 1025-1046 | Received 17 Oct 2001, Accepted 02 Dec 2001, Published online: 14 Feb 2007



Full Article







**Metrics** 

Reprints & Permissions

Read this article



## **ABSTRACT**

In Alberta, oil sands bitumen is utilized for synthetic crude oil (SCO) production by surface mining, bitumen extraction followed by primary (coking) and secondary (catalytic hydrotreating) upgrading processes. SCO is further refined in specially designed or slightly modified conventional refineries into transportation fuels. Oil sands tailings, composed of water, sands, silt, clay and residual bitumen, is produced as a byproduct of the bitumen extraction process. The tailings have poor consolidation and water release characteristics. For twenty years, significant research has been performed to improve the consolidation and water release characteristics of the tailings. Several processes were developed for the management of oil sands tailings, resulting in different recovered water characteristics, consolidation rates and consolidated solid characteristics. These processes may affect the performance of the overall plant operations. Apex Engineering Inc. (AEI) has been developing a process for the same purpose. In this process oil sands tailings are treated with Ca(OH)<sub>2</sub> lime and CO<sub>2</sub> and thickened using a suitable thickener. The combination of chemical treatment

and the use of a thickener results in the release of process water in short retention times without accumulation of any ions in the recovered water. This makes it possible to recycle the recovered water, probably after a chemical treatment, as warm as possible, which improves the thermal efficiency of the extraction process. The AEI Process can be applied in many different fashions for the management of different fractions of the tailings effluent, depending on the overall plant operating priorities.

## **ACKNOWLEDGMENTS**

The authors greatly appreciate the financial support provided by IRAP, NRC Canada (Contract Number: 28565U), Syncrude Canada Ltd.'s courtesy in providing tailings samples and the technical advice provided by Bill Shaw, Ted Kizior, Michael Rogers and Wayne McKee of Syncrude Canada Ltd. Gilbert Wong and Ken Leung of the Geotechnical Group of the University of Alberta diligently and carefully performed the experimental program.



Information for

**Authors** 

**R&D** professionals

**Editors** 

Librarians

**Societies** 

Opportunities

Reprints and e-prints

Advertising solutions

Accelerated publication

Corporate access solutions

Open access

Overview

Open journals

**Open Select** 

**Dove Medical Press** 

F1000Research

Help and information

Help and contact

Newsroom

All journals

Books

## Keep up to date

Register to receive personalised research and resources by email



Sign me up











Accessibility



Copyright © 2025 Informa UK Limited Privacy policy Cookies Terms & conditions



Registered in England & Wales No. 01072954 5 Howick Place | London | SW1P 1WG