



International Wood Products Journal >

Volume 2, 2011 - [Issue 2](#)

149 | 16 | 0
Views | CrossRef citations to date | Altmetric

Original Article

Scheffer index as preferred method to define decay risk zones for above ground wood in building codes

P I Morris & J Wang

Pages 67-70 | Received 15 Apr 2011, Accepted 07 Jul 2011, Published online: 12 Nov 2013

Cite this article <https://doi.org/10.1179/2042645311Y.0000000012>

Sample our
Physical Sciences
Journals



>> [Sign in here](#) to start your access
to the latest two volumes for 14 days

Full Article

Figures & data

References

Citations

Metrics

Reprints & Permissions

Read this article

Share

Abstract

Building codes and wood preservation standards are gradually taking more account of variations in climate within and across national boundaries. In Canada, the NRC-IRC Moisture Index (MI) has been used to delineate the boundary of zones where above ground wood exposed to precipitation or conducive to moisture accumulation needs to be preservative treated to Canadian Standards Association wood preservation standards. However, the older Scheffer Index is more widely recognised in wood science circles. Above ground field test data were reviewed for experiments where matched material had been exposed at more than one test site for a sufficient period for decay to occur. The relative condition of this material at two sites was compared to the Scheffer Index values for the sites and whether the MI values were below or above

1·0. The Scheffer Index was found to be a more reliable predictor of decay condition for above ground outdoor wood applications.

Keywords:

- Wood
- Decay
- Climate
- Building codes

FPIInnovations would like to thank its industry members, Natural Resources Canada, and the Provinces of British Columbia, Alberta, Saskatchewan, Manitoba Ontario, Quebec, New Brunswick, Nova Scotia, and Newfoundland and Labrador, for their guidance and financial support for this research. FPIInnovations would also like to acknowledge its contract clients, Wood Preservation Canada, Timber Specialties Co. and Arch Wood Protection for permission to reproduce some of the data presented here. The authors would like to thank Steve Cornick for invaluable assistance in understanding the MI.

Related research ⓘ

People also read

Recommended articles

Cited by
16

Numerical study on the effects of macro climate and detailing on the relative decay hazard of Norway spruce >

Jonas Niklewski et al.
Wood Material Science & Engineering
Published online: 25 Apr 2019



Information for

[Authors](#)

[R&D professionals](#)

[Editors](#)

[Librarians](#)

[Societies](#)

Opportunities

[Reprints and e-prints](#)

[Advertising solutions](#)

[Accelerated publication](#)

[Corporate access solutions](#)

Open access

[Overview](#)

[Open journals](#)

[Open Select](#)

[Dove Medical Press](#)

[F1000Research](#)

Help and information

[Help and contact](#)

[Newsroom](#)

[All journals](#)

[Books](#)

Keep up to date

Register to receive personalised research and resources by email



Sign me up



Copyright © 2025 Informa UK Limited [Privacy policy](#) [Cookies](#) [Terms & conditions](#)

[Accessibility](#)

 Taylor and Francis Group

Registered in England & Wales No. 01072954
5 Howick Place | London | SW1P 1WG